



## Material - AFNOR NF GX4CrNi13-4

## **Standard Specification for Steel Castings for Pressure Purposes**

**Group - Ferrous Mild Steel Alloys** 

Sub Group - AFNOR NF GX4CrNi13-4 Steel Castings for Pressure Purposes

Application - Intended for Valve, Pump, General Engineering, Automotive and Other Industries

**Grade Belongs to the Industry - Casting** 

Chemical Composition			Heat Treatment	
Carbon	C %	0.060 max.		
Silicon	Si %	1.000 max.	Normalizing or Quenching or Solution Annealing	
Manganese	Mn %	1.000 max.		
Phosphorus	P %	0.035 max.		or Solution Annealing
Sulphur	S %	0.025 max.		
Chromium	Cr %	12.000 - 13.500		
Molybdenum	Mo %	0.700 max.		
Nickel	Ni %	3.500 - 5.000		•
Copper	Cu %	0.300 max.	Mechanical Properties	
Vanadium	V %	0.800 max.	Tensile Strength in Mpa	700 - 960
Iron	Fe %	Balance	Yield Strength in Mpa	500 min.
-	-	-	Elongation in %	12 min.
-	-	-	Reduction of Area in %	-
-	-	-	Hardness in HB	-
-	-		Impac <mark>t in Joule</mark>	27 J @ RT

Cross Reference Table					
Material	Standard	Country	Grade Belong to the Industry		
EN 10213 GX4CrNi13-4	BS	British	Plate, Tubes and Forging		
GX4CrNi13-4	ISO	International	Casting		
1.4317	ISO	International	Casting		
A 743 Grade CA-6NM	ASTM	USA	Casting		
A 743 J91540	ASTM	USA	Casting		
GX4CrNi13-4	UNE	Spain	Casting		
GX4CrNi13-4	PN	Poland	Casting		

Further any inquiry to discuss with Gravity Cast Pvt. Ltd. – Gravity Group of Companies team member Call on +918469160029, or email marketing@gravitycastindia.com

All information in our data sheets and website is indicative only and is not intended to be a substitute for the full specification from which it is extracted. It is intended to provide typical values to allow comparison between metal alloy option rather than a definitive statement of mechanical performance or suitability for a particular application as these will vary with temperature, product type and product application. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of business.