



Material - AISI 1026

Standard Specification For Carbon Steel Compositions For Forging To Hot-Rolled And Cold-Finished Tubing

Group - Ferrous Mild Steel Alloys

Sub Group - AISI 1026 Carbon Steel Compositions For Forging To Hot-Rolled And Cold-Finished Tubing Application - Intended for Valve, Pump, General Engineering, Automotive and Other Industries Grade Belongs to the Industry - Tubing

| Chemical Composition | | | Heat Treatment | |
|----------------------|------|---------------|---|-------------------------|
| Carbon | C % | 0.220 - 0.280 | | |
| Manganese | Mn % | 0.600 - 0.900 | As Raw or Annealing or Normalizing or Hardening and Tempering | |
| Phosphorus | P % | 0.035 max. | | lizing or Hardoning and |
| Sulphur | S % | 0.035 max. | | · · |
| Iron | Fe % | Balance | | ıg |
| - | - | - | | |
| - | - | - | | |
| - | - | - | | |
| - | /- | - | Mechanical Properties | |
| - | - | - | Tensile Strength in Mpa | 415 min. |
| - | - | - | Yield Strength in Mpa | 240 min |
| - | - | - | Elongation in % | 5 min. |
| - | - | - | Reduction of Area in % | 40 - 49 |
| - | - | - | Hardness in HB | 126 - 143 |
| - | - | - | Impact in Joule | - |
| - | | | | |

| Cross Reference Table | | | | |
|-----------------------|----------|---------|---|--|
| Material | Standard | Country | Grade Belong to the Industry | |
| G10260 | UNS | USA | Bars, Wire Rods, Plates, Strip, Sheets and Tubing | |
| 1026 | SAE | USA | Steel | |
| A 1040 1026 | ASTM | USA | Steel | |
| A 29 1026 | ASTM | USA | Steel and Bar | |
| A 510 1026 | ASTM | USA | Wire Rod and Round Wire | |
| A 512 Grade 1026 | ASTM | USA | Tubing | |
| A 513 Grade 1026 | ASTM | USA | Tubing | |

Further any inquiry to discuss with Gravity Cast Pvt. Ltd. – Gravity Group of Companies team member Call on +918469160029, or email marketing@gravitycastindia.com

All information in our data sheets and website is indicative only and is not intended to be a substitute for the full specification from which it is extracted. It is intended to provide typical values to allow comparison between metal alloy option rather than a definitive statement of mechanical performance or suitability for a particular application as these will vary with temperature, product type and product application. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of business.