

Material - AMS 430

Standard Specification for Chromium and Chromium-Nickel Stainless Steel Plate, Sheet and Strip for Pressure Vessels and for General Applications

Group - Ferrous Stainless Steel Alloys

Sub Group - AMS 430 Chromium and Chromium-Nickel Stainless Steel for Pressure Vessels and for General Applications

Application - Intended for Valve, Pump, General Engineering, Automotive and Other Industries Grade Belongs to the Industry - Sheet, Bar, Wire, Shape and Forging

Chemical Composition		Heat Treatment	
C %	0.120 max.		
Si %	1.000 max.		
Mn %	1.000 max.		
P %	0.040 max.	Annealing or Hardening + Tempering	
S %	0.030 max.		
Cr %	16.000 - 18.000		
Fe %	Balance		
-	-		
-	-	Mechanical Properties	
-	-	Tensile Strength in Mpa	448 min.
-	-	Yield Strength in Mpa	241 min.
-	-	Elongation in %	15 min.
-	-	Reduction of Area in %	-
-	-	Hardness in BHN	-
-		Impact in Joule	-
	C % Si % Mn % P % S % Cr % Fe %	C % 0.120 max. Si % 1.000 max. Mn % 1.000 max. P % 0.040 max. S % 0.030 max. Cr % 16.000 - 18.000 Fe % Balance	C % 0.120 max. Si % 1.000 max. Mn % 1.000 max. P % 0.040 max. S % 0.030 max. Cr % 16.000 - 18.000 Fe % Balance - - -<

Cross Reference Table				
Material	Standard	Country Grade Belong to the Industry		
A240 UNS S43000	ASTM	USA	Steel, Plate, Sheet and Strip	
430	AISI	USA	Steel	
430	AS	Australia	Steel, Sheet, Plate and Strip	
430	SAE	USA	Sheet, Bar, Wire, Shape and Forging	
STS 430	KS	Korea	Steel, Sheet, Plate and Strip	
SUS 430	JIS	Japan	Steel, Wire and Bar	
A182 F 430	ASTM	USA	Steel, Pipe and Forging	

Further any inquiry to discuss with Gravity Cast Pvt. Ltd. – Gravity Group of Companies team member Call on +918469160029, or email marketing@gravitycastindia.com

All information in our data sheets and website is indicative only and is not intended to be a substitute for the full specification from which it is extracted. It is intended to provide typical values to allow comparison between metal alloy option rather than a definitive statement of mechanical performance or suitability for a particular application as these will vary with temperature, product type and product application. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of business.