



Material - ASME SA-29 12L14

Standard Specification For Carbon Steel Compositions For Forging To Hot-Rolled And Cold-Finished Steel

Group - Ferrous Mild Steel Alloys

Sub Group - ASME SA-29 12L14 Carbon Steel Compositions For Forging To Hot-Rolled And Cold-Finished Steel Application - Intended for Valve, Pump, General Engineering, Automotive and Other Industries Grade Belongs to the Industry - Steel

Chemical Composition		Heat Treatment	
C %	0.150 max.	As Raw or Annealing or Normalizing or Hardening and Tempering	
Mn %	0.850 - 1.150		
Р%	0.040 - 0.090		lizing or Hardoning and
S %	0.260 - 0.350		· ·
Pb %	0.150 - 0.350		
Fe %	Balance		
-	-		
-	-		
/ -	-	Mechanical Properties	
-	-	Tensile Strength in Mpa	390 - 540
-	-	Yield Strength in Mpa	230 min.
-	-	Elongation in %	10 min.
-	-	Reduction of Area in %	35 - 45
-	-	Hardness in HB	121 - 163
-	-	Impact in Joule	-
	C % Mn % P % S % Pb % Fe %	C % 0.150 max. Mn % 0.850 - 1.150 P % 0.040 - 0.090 S % 0.260 - 0.350 Pb % 0.150 - 0.350 Fe % Balance	C % 0.150 max. Mn % 0.850 - 1.150 P % 0.040 - 0.090 S % 0.260 - 0.350 Pb % 0.150 - 0.350 Fe % Balance - - - Tensile Strength in Mpa Yield Strength in Mpa Yield Strength in Mpa Elongation in % Reduction of Area in % Hardness in HB

Cross Reference Table				
Material	Standard	Country Grade Belong to the Industry		
G12140	UNS	USA	Bars, Wire Rods, Plates, Strip, Sheets and Tubing	
12L14	SAE	USA	Bars, Wire Rods, Plates, Strip, Sheets and Tubing	
12L14	AISI	USA	Steel and Bar	
A 1040 12L14	ASTM	USA	Steel	
A 510 12L14	ASTM	USA	Wire Rod, Round Wire and Steel	
A 519 12L14	ASTM	USA	Tubing	
A 576 12L14	ASTM	USA	Steel and Bar	

Further any inquiry to discuss with Gravity Cast Pvt. Ltd. – Gravity Group of Companies team member Call on +918469160029, or email marketing@gravitycastindia.com

All information in our data sheets and website is indicative only and is not intended to be a substitute for the full specification from which it is extracted. It is intended to provide typical values to allow comparison between metal alloy option rather than a definitive statement of mechanical performance or suitability for a particular application as these will vary with temperature, product type and product application. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of business.