

Material - ASTM A 268 26-3-3

Standard Specification for Chromium and Chromium-Nickel Stainless Steel Plate, Sheet, and Strip for Pressure Vessels and for General Applications

Group - Ferrous Stainless Steel Alloys

Sub Group - ASTM A 268 26-3-3 Chromium and Chromium-Nickel Stainless Steel for Pressure Vessels and for General Applications

Application - Intended for Valve, Pump, General Engineering, Automotive and Other Industries Grade Belongs to the Industry - Steel and Tube

Chemical Composition			Heat Treatment	
Carbon	C %	0.030 max.		
Silicon	Si %	1.000 max.		
Manganese	Mn %	1.000 max.		
Phosphorus	Ρ%	0.040 max.	Annealing or Hardening + Tempering	
Sulphur	S %	0.030 max.		
Chromium	Cr %	25.000 - 28.000	<i>.</i>	
Molybdenum	Mo %	3.000 - 3.500		
Nickel	Ni %	1.000 - 3.500		
Nitrogen	N %	0.040 max.	Mechanical Properties	
Titanium	Ti %	0.200 - 1.000	Tensile Strength in Mpa	585 min.
Iron	Fe %	Balance	Yield Strength in Mpa	450 min.
-	-	-	Elongation in %	11 min.
-	-	-	Reduction of Area in %	-
-	-	-	Hardn <mark>ess in HB</mark>	265 max.
-	-	-	Impac <mark>t in Joule</mark>	-
		-		

Cross Reference Table				
Material	Standard	Country Grade Belong to the Industry		
A240 UNS S44660	ASTM	USA	Steel, Plate, Sheet and Strip	
S446660	UNS	USA	Steel	
A176 S44660	ASTM	USA	Steel, Sheet, Plate and Strip	
SA-240 UNS S44660	ASME	USA	Steel	
A959 Type 26-3-3	ASTM	USA	Steel	
SA-803 26-3-3	ASME	USA	Steel and Tube	
SA-240 Type 26-3-3	ASME	USA	Steel, Sheet, Plate and Strip	

Further any inquiry to discuss with Gravity Cast Pvt. Ltd. – Gravity Group of Companies team member Call on +918469160029, or email marketing@gravitycastindia.com

All information in our data sheets and website is indicative only and is not intended to be a substitute for the full specification from which it is extracted. It is intended to provide typical values to allow comparison between metal alloy option rather than a definitive statement of mechanical performance or suitability for a particular application as these will vary with temperature, product type and product application. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of business.

ONE STOP SOLUTION FOR METAL PARTS