

Material - ASTM A 29 1008

Standard Specification For Carbon Steel Compositions For Forging To Hot-Rolled And Cold-Finished Bars, To Wire Rods, Plates, Strip, Sheets, Tubing

Group - Ferrous Mild Steel Alloys

Sub Group - ASTM A 29 1008 Carbon Steel Compositions For Forging To Hot-Rolled And Cold-Finished Bars, Wire Rods, Plates, Strip, Sheets and Tubing

Application - Intended for Valve, Pump, General Engineering, Automotive and Other Industries Grade Belongs to the Industry - Bars, Wire Rods, Plates, Strip, Sheets and Tubing

Chemical Composition			Heat Treatment	
Carbon	C %	0.100 max.		
Manganese	Mn %	0.300 - 0.500	As Raw or Annealing or Normalizing or Hardening and Tempering	
Phosphorus	Р%	0.040 max.		
Sulphur	S %	0.050 max.		
Boron	В %	0.0005 - 0.003		
Copper	Cu %	0.100 max.		
Niobium	Nb %	0.025 max.		
Vanadium	V %	0.050 max.		
Silicon	Si %	0.100 max.	Mechanical Properties	
Aluminium	Al %	0.020 max.	Tensile Strength in Mpa	260 - 655
Iron	Fe %	Balance	Yield Strength in Mpa	160 min.
-	-	-	Elongation in %	20 min.
-	-	-	Reduction of Area in %	45 - 55
-	-	-	Hardn <mark>ess in HB</mark>	86 - 95
-	-	-	Impac <mark>t in Joule</mark>	-

Cross Reference Table				
Material	Standard	Country	Grade Belong to the Industry	
G10080	UNS	USA	Bars, Wire Rods, Plates, Strip, Sheets and Tubing	
1008	SAE	USA	Bars, Wire Rods, Plates, Strip, Sheets and Tubing	
1008	AISI	USA	Bars, Wire Rods, Plates, Strip, Sheets and Tubing	
A 1040 1008	ASTM	USA	Bars, Wire Rods, Plates, Strip, Sheets and Tubing	
A 108 Grade 1008	ASTM	USA	Bars, Wire Rods, Plates, Strip, Sheets and Tubing	
A 29 M1008	ASTM	USA	Bars, Wire Rods, Plates, Strip, Sheets and Tubing	
A 510 1008	ASTM	USA	Bars, Wire Rods, Plates, Strip, Sheets and Tubing	

Further any inquiry to discuss with Gravity Cast Pvt. Ltd. – Gravity Group of Companies team member Call on +918469160029, or email marketing@gravitycastindia.com

All information in our data sheets and website is indicative only and is not intended to be a substitute for the full specification from which it is extracted. It is intended to provide typical values to allow comparison between metal alloy option rather than a definitive statement of mechanical performance or suitability for a particular application as these will vary with temperature, product type and product application. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of business.

ONE STOP SOLUTION FOR METAL PARTS