



## Material - ASTM A 682 Grade 1086

Standard Specification For Carbon Steel Compositions For Forging To Hot-Rolled Steel and Strip

**Group - Ferrous Mild Steel Alloys** 

Sub Group - ASTM A 682 Grade 1086 Carbon Steel Compositions For Forging To Hot-Rolled Steel and Strip Application - Intended for Valve, Pump, General Engineering, Automotive and Other Industries Grade Belongs to the Industry - Steel and Strip

Chemical Composition			Heat Treatment	
Carbon	C %	0.800 - 0.930		
Manganese	Mn %	0.300 - 0.500	As Raw or Annealing or Normalizing or Hardening and Tempering	
Phosphorus	P %	0.030 max.		lizing or Hardoning and
Sulphur	S %	0.035 max.		<b>°</b>
Silicon	Si %	0.150 - 0.300		ing .
Iron	Fe %	Balance		
-	-	-		
-	-	-		
-	-	-	Mechanical Properties	
-	-	-	Tensile Strength in Mpa	670 - 770
-	-	-	Yield Strength in Mpa	420 min.
	-	-	Elongation in %	10 min.
-	-	-	Reduction of Area in %	25 - 40
-	-	-	Hardn <mark>ess in HB</mark>	192 - 229
-	-	-	Impa <mark>ct in Joule</mark>	-

Cross Reference Table				
Material	Standard	Country Grade Belong to the Industry		
G10860	UNS	USA	Bars, Wire Rods, Plates, Strip, Sheets and Tubing	
1086	SAE	USA	Steel	
1086	AISI	USA	Steel and Bar	
A 713 G10860	ASTM	USA	Steel and Wire	
A 682 G10860	ASTM	USA	Steel and Strip	
A 1040 1086	ASTM	USA	Steel	
A 684 Grade 1086	ASTM	USA	Steel and Strip	

## Further any inquiry to discuss with Gravity Cast Pvt. Ltd. – Gravity Group of Companies team member Call on +918469160029, or email marketing@gravitycastindia.com

All information in our data sheets and website is indicative only and is not intended to be a substitute for the full specification from which it is extracted. It is intended to provide typical values to allow comparison between metal alloy option rather than a definitive statement of mechanical performance or suitability for a particular application as these will vary with temperature, product type and product application. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of business.

## **ONE STOP SOLUTION FOR METAL PARTS**