



## Material - ASTM A176 Type 422

Standard Specification for Stainless and Heat Resisting Chromium Steel Plate, Sheet and Strip

**Group - Ferrous Stainless Steel Alloys** 

Sub Group - ASTM A176 Type 422 Stainless and Heat Resisting Chromium Steel Plate, Sheet and Strip Application - Intended for Valve, Pump, General Engineering, Automotive and Other Industries Grade Belongs to the Industry - Plate, Sheet and Strip

Chemical Composition			Heat Treatment	
Carbon	C %	0.200 - 0.250		
Silicon	Si %	0.500 max.		
Manganese	Mn %	0.500 - 1.000		
Phosphorus	P %	0.025 max.	Annealing or Hardening + Tempering	ng + Tempering
Sulphur	S %	0.025 max.		
Chromium	Cr %	11.000 - 12.500		
Nickel	Ni %	0.500 - 1.000		
Molybdenum	Mo %	0.900 - 1.250		
Vanadium	V %	0.200 - 0.300	Mechanical Properties	
Tungsten	W %	0.900 - 1.250	Tensile Strength in Mpa	-
Iron	Fe %	Balance	Yield Strength in Mpa	-
-	-	-	Elongation in %	-
-	-	-	Reduction of Area in %	-
-	-	-	Hardness in HRC	24 max.
-	-	-	Impact in Joule	-

Cross Reference Table					
Material	Standard	Country	Grade Belong to the Industry		
1.4935	DIN	Germany	Casting		
SUH 616	JIS	Japan	Bar and Wire		
20 VNiMoCr 120	STAS	Romania	Casting		
S 42100	UNS	USA	Casting		
X 20 CrMoWV 12-1	DIN	Germany	Casting		
422	AISI	USA	Bar, Wire, Shapes and Forging		
A743 CA28MWV	ASTM	USA	Casting		

Further any inquiry to discuss with Gravity Cast Pvt. Ltd. – Gravity Group of Companies team member Call on +918469160029, or email marketing@gravitycastindia.com

All information in our data sheets and website is indicative only and is not intended to be a substitute for the full specification from which it is extracted. It is intended to provide typical values to allow comparison between metal alloy option rather than a definitive statement of mechanical performance or suitability for a particular application as these will vary with temperature, product type and product application. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of business.