



## **Material - ASTM A351 CF3MN**

## Standard Specification for Castings, Austenitic, for Pressure-Containing Parts

**Group - Ferrous Stainless Steel Alloys** 

Sub Group - ASTM A351 / 351M Castings, Austenitic, for Pressure-Containing Parts
Application - Intended for Valves, Pumps, General Engineering, Automobile and Other Industries
Grade Belongs to the Industry - Casting

Chemical Composition			Heat Treatment	
Carbon	C %	0.030 max.		
Silicon	Si %	1.500 max.		
Manganese	Mn %	1.500 max.	Solution Annealing	
Phosphorus	P %	0.040 max.		
Sulphur	S %	0.040 max.		
Chromium	Cr %	17.000 - 21.000		
Nickel	Ni %	9.000 - 13.000		
Molybdenum	Mo %	2.000 - 3.000		
Nitrogen	N %	0.100 - 0.200	Mechanical Properties	
Iron	Fe %	Balance	Tensile Strength in Mpa	515 min.
-	-		Yield Strength in Mpa	255 min.
-	-	-	Elongation in %	35 min.
-	-	-	Reduction of Area in %	-
-	-		Hardness in BHN	-
-	-	-	Impac <mark>t in Joule</mark>	-

Cross Reference Table				
Material	Standard	Country	Grade Belong to the Industry	
A743 CF3MN	ASTM	USA	Casting	
316L	AISI	USA	Bar, Wire, Strip, Plate, Sheet and Forging	
1.4404	DIN	Germany	Cold Rolled, Strips, Slit Coils and Sheets	
1.4404	EN	European Union	Rod, Bars, Wire and Forging	
316 S 11	BS	British	Bright Bars, Hot Rolled and Cold Rolled Coil	
SUS 316L	JIS	Japan	Hot Rolled Equal Leg Angles	
03CH17N14M3	GOST	Russia	Pipes, Fittings, Bar, Sheet and Forging	

Further any inquiry to discuss with Gravity Cast Pvt. Ltd. – Gravity Group of Companies team member Call on +918469160029, or email marketing@gravitycastindia.com

All information in our data sheets and website is indicative only and is not intended to be a substitute for the full specification from which it is extracted. It is intended to provide typical values to allow comparison between metal alloy option rather than a definitive statement of mechanical performance or suitability for a particular application as these will vary with temperature, product type and product application. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of business.