



Material - BS 10216-2 EN P 195 GH

Standard Specification for Seemless Steel Tubes for Pressure Purposes

Group - Ferrous Mild Steel Alloys

Sub Group - BS 10216-2 Seemless Steel Tubes for Pressure Purposes

Application - Intended for Valve, Pump, General Engineering, Automotive and Other Industries

Grade Belongs to the Industry - Steel and Tube

Chemical Composition			Heat Treatment	
Carbon	C %	0.130 max.		
Silicon	Si %	0.350 max.		
Manganese	Mn %	0.700 max.	Normalising Forming	
Phosphorus	P %	0.025 max.		
Sulphur	S %	0.020 max.		
Chromium	Cr %	0.300 max.		
Nickel	Ni %	0.300 max.		
Molybdenum	Mo %	0.080 max.		
Copper	Cu %	0.300 max.	Mechanical Properties	
Aluminium	Al %	0.020 max.	Tensile Strength in Mpa	320 - 440
Niobium	Nb %	0.010 max.	Yield Strength in Mpa	195 min.
Titanium	Ti %	0.040 max.	Elongation in %	25 min.
Vanadium	V %	0.020 max.	Reduction of Area in %	-
Cr + Cu + Mo + Ni	CI % + Cu %	0.700 max.	Hardness in BHN	-
Iron	Fe %	Balance	Impact in Joule	27 min. @ RT

Cross Reference Table				
Material	Standard	Country	Grade Belong to the Industry	
1.0348	EN	European Union	Steel and Tube	
UHI/ P195GH	DIN	Germany	Casting	
1.0348	BS	British	Steel and Tube	
1.0348	DIN	Germany	Steel and Tube	
1004	AS	Australia	Steel and Tube	
10848	GOST	Russia	Sheet and Strip	
2C10	UNI	Italy	Plate, Sheet, Strip, Coil and Flats	

Further any inquiry to discuss with Gravity Cast Pvt. Ltd. – Gravity Group of Companies team member Call on +918469160029, or email marketing@gravitycastindia.com

All information in our data sheets and website is indicative only and is not intended to be a substitute for the full specification from which it is extracted. It is intended to provide typical values to allow comparison between metal alloy option rather than a definitive statement of mechanical performance or suitability for a particular application as these will vary with temperature, product type and product application. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of business.