



## Material - BS 10216-5 EN X5CrNiMo17-12-2

## Standard Specification for Seemless Steel Tubes for Pressure Purposes

**Group - Ferrous Stainless Steel Alloys** 

Sub Group - BS 10216-5 Seemless Steel Tubes for Pressure Purposes

Application - Intended for Valve, Pump, General Engineering, Automotive and Other Industries

**Grade Belongs to the Industry - Tube** 

Chemical Composition			Heat Treatment	
Carbon	C %	0.070 max.		
Silicon	Si %	1.000 max.		
Manganese	Mn %	2.000 max.	Solution Annealing	
Phosphorus	P %	0.040 max.		
Sulphur	S %	0.015 max.		
Chromium	Cr %	16.500 - 18.500		
Nickel	Ni %	10.000 - 13.000		
Molybdenum	Mo %	2.000 - 2.500		
Nitrogen	N %	0.110 max.	Mechanical Properties	
Iron	Fe %	Balance	Tensile Strength in Mpa	510 - 710
-	-		Yield Strength in Mpa	205 min.
-	-	-	Elongation in %	30 min.
-	-	-	Reduction of Area in %	-
-	-	-	Hardness in BHN	-
-	-	-	Impac <mark>t in Joule</mark>	60 min. @ -196°C

Cross Reference Table				
Material	Standard	Country	Grade Belong to the Industry	
316L	AISI	USA	Bar, Wire, Strip, Slit, Plate, Sheet and Forging	
1.4404	BS	British	Cold Rolled, Strips, Slit Coils and Sheets	
1.4404	EN	European Union	Rod, Bars, Wire and Forging	
316 S 11	BS	British	Bright Bars, Hot Rolled and Cold Rolled Coil	
SUS 316L	JIS	Japan	Hot Rolled Equal Leg Angles	
03CH17N14M3	GOST	Russia	Pipes, Fittings, Bar, Sheet and Forging	
ASTM A 351 CF3M	ASTM	USA	Casting	

Further any inquiry to discuss with Gravity Cast Pvt. Ltd. – Gravity Group of Companies team member Call on +918469160029, or email marketing@gravitycastindia.com

All information in our data sheets and website is indicative only and is not intended to be a substitute for the full specification from which it is extracted. It is intended to provide typical values to allow comparison between metal alloy option rather than a definitive statement of mechanical performance or suitability for a particular application as these will vary with temperature, product type and product application. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of business.