



Material - BS 309C30

Standard Specification for Heat Resisting Stainless Steel; Steel Castings for General Engineering Purposes

Group - Ferrous Stainless Steel Alloys

Sub Group - BS 309C30 Heat Resisting Stainless Steel; Steel Castings for General Engineering Purposes Application - Intended for Valve, Pump, General Engineering, Automotive and Other Industries Grade Belongs to the Industry - Casting

Chemical Composition			Heat Treatment	
Carbon	C %	0.500 max.		
Silicon	Si %	2.500 max.		
Manganese	Mn %	2.000 max.	As - Cast	
Phosphorus	P %	0.050 max.		
Sulphur	S %	0.050 max.		
Chromium	Cr %	22.000 - 27.000		
Nickel	Ni %	10.000 - 14.000		
Molybdenum	Mo %	1.500 max.		
Iron	Fe %	Balance	Mechanical Properties	
-	-	-	Tensile Strength in Mpa	515 min.
-	-	-	Yield Strength in Mpa	240 min.
-	-	-	Elongation in %	10 min.
-	-	-	Reduction of Area in %	-
-	-	-	Hardness in BHN	
-	-	-	Impact in Joule	-

Cross Reference Table				
Material	Standard	Country	Grade Belong to the Industry	
1.4837	DIN	Germany	Casting	
J93503	UNS	USA	Casting	
SCH 13 A	JIS	Japan	Casting	
422936	CSN	Czech Republic	Casting	
40 CH 24 N 12 SL	GOST	Russia	Casting	
40 CrNiSi 25-12	MSZ	Hungary	Casting	
A297 Grade HH	ASTM	USA	Casting	

Further any inquiry to discuss with Gravity Cast Pvt. Ltd. – Gravity Group of Companies team member Call on +918469160029, or email marketing@gravitycastindia.com

All information in our data sheets and website is indicative only and is not intended to be a substitute for the full specification from which it is extracted. It is intended to provide typical values to allow comparison between metal alloy option rather than a definitive statement of mechanical performance or suitability for a particular application as these will vary with temperature, product type and product application. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of business.