



Material - DIN 1.7720

Standard Specification for Steel Castings for Pressure Purposes

Group - Ferrous Mild Steel Alloys

Sub Group - DIN 1.7720 Steel Castings for Pressure Purposes

Application - Intended for Valve, Pump, General Engineering, Automotive and Other Industries Grade Belongs to the Industry - Casting

Chemical Composition		Heat Treatment	
C %	0.100 - 0.150		
Si %	0.450 max.		
Mn %	0.400 - 0.700	Normalising or Annealing or Hardening + Tempering	
Р%	0.030 max.		
S %	0.020 max.		
Cr %	0.300 - 0.500		
Mo %	0.400 - 0.600		
V %	0.220 - 0.300		
Sn %	0.025 max.	Mechanical Properties	
Fe %	Balance	Tensile Strength in Mpa	510 - 660
-	-	Yield Strength in Mpa	295 min.
-	-	Elongation in %	17 min.
-	-	Reduction of Area in %	-
-	-	Hardness in BHN	-
-	-	Impact in Joule	27 J @ RT
	C % Si % Mn % P % S % Cr % Mo % V % Sn % Fe % - - - -	C % 0.100 - 0.150 Si % 0.450 max. Mn % 0.400 - 0.700 P % 0.030 max. S % 0.020 max. Cr % 0.300 - 0.500 Mo % 0.400 - 0.600 V % 0.220 - 0.300 Sn % 0.025 max. Fe % Balance - - - - - -	C % 0.100 - 0.150 Si % 0.450 max. Mn % 0.400 - 0.700 P % 0.030 max. S % 0.020 max. Cr % 0.300 - 0.500 Mo % 0.400 - 0.600 V % 0.220 - 0.300 Sn % 0.025 max. Fe % Balance - - - Elongation in Mpa - - - - Hardness in BHN

Cross Reference Table				
Material	Standard	Country	Gr <mark>ade Belong</mark> to the Industry	
1.7720	EN	European Union	Casting	
1.772	EN	European Union	Casting	
660	BS	British	Steel and Plates	
G 12 MoCrV 5 2	EN	European Union	Casting	
G 12 MoCrV 5-2	DIN	Germany	Casting	
G12MoCrV5-2	AFNOR NF	France	Casting	
G12MoCrV5-2	UNI	Italy	Casting	

Further any inquiry to discuss with Gravity Cast Pvt. Ltd. – Gravity Group of Companies team member Call on +918469160029, or email marketing@gravitycastindia.com

All information in our data sheets and website is indicative only and is not intended to be a substitute for the full specification from which it is extracted. It is intended to provide typical values to allow comparison between metal alloy option rather than a definitive statement of mechanical performance or suitability for a particular application as these will vary with temperature, product type and product application. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of business.

ONE STOP SOLUTION FOR METAL PARTS