



Material - DIN 15 NiCuMoNb 5 S

Standard Specification for Seemless Steel Tubes for Pressure Purposes

Group - Ferrous Mild Steel Alloys

Sub Group - DIN 15 NiCuMoNb 5 S Seemless Steel Tubes for Pressure Purposes
Application - Intended for Valve, Pump, General Engineering, Automotive and Other Industries
Grade Belongs to the Industry - Steel

Chemical Composition			Heat Treatment	
Carbon	C %	0.100 - 0.170		
Silicon	Si %	0.250 - 0.500		
Manganese	Mn %	0.800 - 0.120	Normalising + Tempering	
Phosphorus	P %	0.016 max.		
Sulphur	S %	0.005 max.		
Chromium	Cr %	0.300 max.		
Molybdenum	Mo %	0.250 - 0.400		
Nickel	Ni %	1.000 - 1.300		
Vanadium	V %	0.020 max.	Mechanical Properties	
Niobium	Nb %	0.015 - 0.025	Tensile Strength in Mpa	580 - 780
Aluminium	Al %	0.050 max.	Yield Strength in Mpa	400 min.
Copper	Cu %	0.500 - 0.800	Elongation in %	16 min.
Nitrogen	N %	0.020 max.	Reduction of Area in %	-
Iron	Fe %	Balance	Hardness in BHN	-
-	-	-	Impac <mark>t in Joule</mark>	41 J @ RT

Cross Reference Table				
Material	Standard	Country	Grade Belong to the Industry	
1.6368	EN	European Union	Steel and Flat	
1.6368	DIN	Germany	Steel and Flat	
1.6368	DIN	Germany	Steel and Flat	
15NiCuMoNb5	DIN	Germany	Steel	
1.6369	DIN	Germany	Steel	
1.6369	DIN	Germany	Steel	
15 NiCuMoNb 5 S	DIN	Germany	Steel	

Further any inquiry to discuss with Gravity Cast Pvt. Ltd. – Gravity Group of Companies team member Call on +918469160029, or email marketing@gravitycastindia.com

All information in our data sheets and website is indicative only and is not intended to be a substitute for the full specification from which it is extracted. It is intended to provide typical values to allow comparison between metal alloy option rather than a definitive statement of mechanical performance or suitability for a particular application as these will vary with temperature, product type and product application. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of business.