



Material - DIN X 6 CrNiMoNb 17 12 2

Standard Specification for Seemless Steel Tubes for Pressure Purposes

Group - Ferrous Stainless Steel Alloys

Sub Group - DIN X 6 CrNiMoNb 17 12 2 Seemless Steel Tubes for Pressure Purposes
Application - Intended for Valve, Pump, General Engineering, Automotive and Other Industries
Grade Belongs to the Industry - Steel, Sheet, Plate and Strip

Chemical Composition			Heat Treatment	
Carbon	С%	0.080 max.		
Silicon	Si %	1.000 max.	Solution Annealing	
Manganese	Mn %	2.000 max.		
Phosphorus	P %	0.040 max.		
Sulphur	S %	0.015 max.		
Chromium	Cr %	16.500 - 18.500		
Molybdenum	Mo %	2.000 - 2.500		
Nickel	Ni %	10.500 - 13.500		-
Niobium	Nb %	1.000 max.	Mechanical Properties	
Iron	Fe %	Balance	Tensile Strength in Mpa	510 - 740
-	-	-	Yield Strength in Mpa	215 min.
-	-	-	Elongation in %	30 min.
-	-	-	Reduction of Area in %	-
-	-		Hardness in HB	230 max.
-	-	-	Impac <mark>t in Joule</mark>	55 J @ RT

Cross Reference Table				
Material	Standard	Country	Grade Belong to the Industry	
1.4580	EN	European Union	Tube	
1.458	DIN	Germany	Steel, Sheet, Plate and Strip	
10216-5	BS	British	Steel, Sheet, Plate and Strip	
X6CrNiMoNb17 12 2	UNE	Spain	Steel, Bar, Wire, Rod and Forging	
X6CrNiMoNb17 12 2 KKW	ONORM	Australia	Steel	
X6CrNiMoNb17-12-2	AFNOR NF	France	Steel, Bar and Rods	
318 S 17	BS	British	Steel and Wire	

Further any inquiry to discuss with Gravity Cast Pvt. Ltd. – Gravity Group of Companies team member Call on +918469160029, or email marketing@gravitycastindia.com

All information in our data sheets and website is indicative only and is not intended to be a substitute for the full specification from which it is extracted. It is intended to provide typical values to allow comparison between metal alloy option rather than a definitive statement of mechanical performance or suitability for a particular application as these will vary with temperature, product type and product application. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of business.