

## Material - DIN X 8 CrNiAlTi 20-20

Standard Specification for Chromium and Chromium-Nickel Stainless Steel Plate, Sheet, and Strip for Pressure Vessels and for General Applications

**Group - Ferrous Stainless Steel Alloys** 

Sub Group - DIN X 8 CrNiAlTi 20-20 Chromium and Chromium-Nickel Stainless Steel for Pressure Vessels and for General Applications

Application - Intended for Valve, Pump, General Engineering, Automotive and Other Industries Grade Belongs to the Industry - Steel

Chemical Composition			Heat Treatment	
Carbon	C %	0.080 max.		
Silicon	Si %	1.000 max.		
Manganese	Mn %	1.000 max.		
Phosphorus	Ρ%	0.030 max.	Solution Annealing	nealing
Sulphur	S %	0.015 max.		
Chromium	Cr %	18.000 - 22.000		
Nickel	Ni %	18.000 - 22.000		
Aluminium	Al %	0.600 max.		
Titanium	Ti %	0.600 max.	Mechanical Properties	
Iron	Fe %	Balance	Tensile Strength in Mpa	-
-	-	-	Yield Strength in Mpa	-
-	-	-	Elongation in %	-
-	-	-	Reduction of Area in %	-
-	-	-	Hardne <mark>ss in BHN</mark>	-
-	-	-	Impac <mark>t in Joule</mark>	-
				-

Cross Reference Table				
Material	Standard	Country	Grade Belong to the Industry	
A240 UNS S33400	ASTM	USA	Steel, Plate, Sheet and Strip	
S22400	UNS	USA	Steel	
A959 Type 334	ASTM	USA	Steel	
1.4847	DIN	Germany	Steel	
1.4847	EN	European Union	Steel	
-	-	-	-	
-	-	-	-	

## Further any inquiry to discuss with Gravity Cast Pvt. Ltd. – Gravity Group of Companies team member Call on +918469160029, or email marketing@gravitycastindia.com

All information in our data sheets and website is indicative only and is not intended to be a substitute for the full specification from which it is extracted. It is intended to provide typical values to allow comparison between metal alloy option rather than a definitive statement of mechanical performance or suitability for a particular application as these will vary with temperature, product type and product application. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of business.

## ONE STOP SOLUTION FOR METAL PARTS