



## **Material - EN 1.4301**

## Standard Specification for Castings, Iron-Chromium-Nickel, Corrosion Resistant, for General Application

**Group - Ferrous Stainless Steel Alloys** 

Sub Group - EN 1.4301 Castings, Iron-Chromium-Nickel, Corrosion Resistant, for General Application Application - Intended for Valve, Pump, General Engineering, Automotive and Other Industries Grade Belongs to the Industry - Casting

Chemical Composition			Heat Treatment	
Carbon	C %	0.070 max.		
Silicon	Si %	1.000 max.		
Manganese	Mn %	2.000 max.		
Phosphorus	P %	0.045 max.	Solution Annealing	
Sulphur	S %	0.015 max.		
Chromium	Cr %	17.500 - 19.500		
Nickel	Ni %	8.000 - 10.500		
Nitrogen	N %	0.100 max.		
Iron	Fe %	Balance	Mechanical Properties	
-	-	-	Tensile Strength in Mpa	500 - 2300
-	-	-	Yield Strength in Mpa	225 min.
-	-	-	Elongation in %	1 min.
-	-	-	Reduction of Area in %	-
-	-	-	Hardness in BHN	-
-	-	-	Impact in Joule	60 J @ RT

Cross Reference Table				
Material	Standard	Country	try Grade Belong to the Industry	
1.4308	DIN	Germany	Casting	
304	AISI	USA	Bar, Wire, Strip, Plat, Sheet and Forging	
304 S11	BS	British	Bright Bars, Hot Rolled and Cold Rolled, Coil	
SUS 304	JIS	Japan	Hot Rolled Equal Leg Angles	
08CH18N10	GOST	Russia	Pipes, Fittings, Bar, Sheet and Forging	
A743 CF8	ASTM	USA	Casting	
A351 CF8	ASTM	USA	Casting	

Further any inquiry to discuss with Gravity Cast Pvt. Ltd. – Gravity Group of Companies team member Call on +918469160029, or email marketing@gravitycastindia.com

All information in our data sheets and website is indicative only and is not intended to be a substitute for the full specification from which it is extracted. It is intended to provide typical values to allow comparison between metal alloy option rather than a definitive statement of mechanical performance or suitability for a particular application as these will vary with temperature, product type and product application. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of business.