

## Material - EN 10083-3 1.7182

## Standard Specification for Mild Steel Alloys Bar and Rod

Group - Ferrous Mild Steel Alloys

Sub Group - EN 10083-3 1.7182 Mild Steel Alloys Bar and Rod

Application - Intended for Valve, Pump, General Engineering, Automotive and Other Industries Grade Belongs to the Industry - Bar and Rod

**Chemical Composition Heat Treatment** C % 0.240 - 0.300 Carbon Silicon Si % 0.400 max. Mn % 1.100 - 1.140 Manganese As Raw or Annealing or Normalizing or Hardening and Phosphorus Ρ% 0.025 max. Tempering Sulphur S % 0.035 max. Chromium 0.300 - 0.600 Cr % Boron B % 0.0008 - 0.0050 Iron Fe % Balance **Mechanical Properties** \_ \_ \_ Tensile Strength in Mpa 800 - 100 \_ Yield Strength in Mpa \_ 700 min. \_ Elongation in % 15 min. \_ \_ \_ **Reduction of Area in %** -\_ \_ Hardness in BHN As Per HT \_ \_ \_ Impact in Joule 65 J @ RT

Cross Reference Table			
Material	Standard	Country	Grade Belong to the Industry
27MnCrB5-2	EN	European Union	Bar and Rod
27MnCrB5-2	ISO	International	Bar and Rod
1.7182	DIN	Germany	Bar and Rod
27MnCrB5-2	DIN	Germany	Bar and Rod
1.7182	SFS	Finland	Bar and Rod
27MnCrB5-2	SFS	Finland	Bar and Rod
1.7182	CSN	Czech Republic	Bar and Rod

## Further any inquiry to discuss with Gravity Cast Pvt. Ltd. – Gravity Group of Companies team member Call on +918469160029, or email marketing@gravitycastindia.com

All information in our data sheets and website is indicative only and is not intended to be a substitute for the full specification from which it is extracted. It is intended to provide typical values to allow comparison between metal alloy option rather than a definitive statement of mechanical performance or suitability for a particular application as these will vary with temperature, product type and product application. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of business.

## ONE STOP SOLUTION FOR METAL PARTS