

## Material - EN X3CrNiMo13-4

Standard Specification for Steel Castings for General Engineering Purposes

Group - Ferrous Stainless Steel Alloys

Sub Group - EN X3CrNiMo13-4 Steel Castings for General Engineering Purposes

Application - Intended for Valve, Pump, General Engineering, Automotive and Other Industries Grade Belongs to the Industry - Casting

Chemical Composition		Heat Treatment	
C %	0.050 max.	As Cast or Annealing or Normalizing or Hardening and Tempering	
Si %	0.700 max.		
Mn %	1.500 max.		alizing or Hardoning and
Ρ%	0.040 max.		ů ů
S %	0.015 max.		
Cr %	12.000 - 14.000		
Ni %	3.500 - 4.500		
Mo %	0.300 - 0.700		
N %	0.020 max.	Mechanical Properties	
Fe %	Balance	Tensile Strength in Mpa	650 - 1100
-	-	Yield Strength in Mpa	520 min.
-	-	Elongation in %	10 min.
-	-	Reduction of Area in %	-
-	-	Hardness in BHN	320 max.
-	-	Impac <mark>t in Joule</mark>	40 J @ RT
	C % Si % Mn % P % S % Cr % Ni % Mo % N % Fe % - - - - - - -	C % 0.050 max.   Si % 0.700 max.   Mn % 1.500 max.   P % 0.040 max.   S % 0.015 max.   Cr % 12.000 - 14.000   Ni % 3.500 - 4.500   Mo % 0.020 max.   Fe % Balance   - -   - -   - -	C % 0.050 max.   Si % 0.700 max.   Mn % 1.500 max.   P % 0.040 max.   S % 0.015 max.   Cr % 12.000 - 14.000   Ni % 3.500 - 4.500   Mo % 0.020 max.   Fe % Balance   - -   - Elongation in %   - -   N % -   - Hardness in BHN

Cross Reference Table				
Material	Standard	Country	Grade Belong to the Industry	
425C11	BS	British	Casting	
2074/H3C	AS	Australia	Casting	
2074/H3CM	AS	Australia	Casting	
Z 4 CN 13.4 M	AFNOR NF	France	Casting	
Z 4 CND 13.4 M	AFNOR NF	France	Casting	
1.4313	EN	European Union	Casting	
1.4313	AFNOR NF	France	Casting	

## Further any inquiry to discuss with Gravity Cast Pvt. Ltd. – Gravity Group of Companies team member Call on +918469160029, or email marketing@gravitycastindia.com

All information in our data sheets and website is indicative only and is not intended to be a substitute for the full specification from which it is extracted. It is intended to provide typical values to allow comparison between metal alloy option rather than a definitive statement of mechanical performance or suitability for a particular application as these will vary with temperature, product type and product application. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of business.

## **ONE STOP SOLUTION FOR METAL PARTS**