



Material - ISO X 12 CrMo 51

Standard Specification for Seemless Steel Tubes for Pressure Purposes

Group - Ferrous Alloy Steel

Sub Group - ISO X 12 CrMo 51 Seemless Steel Tubes for Pressure Purposes
Application - Intended for Valve, Pump, General Engineering, Automotive and Other Industries

Grade Belongs to the Industry - Steel, Forging, Rolling and Bar

Chemical Composition			Heat Treatment	
Carbon	C %	0.080 - 0.150		
Silicon	Si %	0.500 max.		
Manganese	Mn %	0.300 - 0.600	Isothermal Annealing	
Phosphorus	P %	0.035 max.		
Sulphur	S %	0.030 max.		
Chromium	Cr %	4.000 - 6.000		
Molybdenum	Mo %	0.450 - 0.650		
Iron	Fe %	Balance		-
-	-	-	Mechanical Properties	
-	-		Tensile Strength in Mpa	430 - 580
-	-	-	Yield Strength in Mpa	175 min.
-	-	-	Elongation in %	18 min.
-	-	-	Reduction of Area in %	-
-	-	-	Hardness in BHN	-
-	-		Impac <mark>t in Joule</mark>	27 J @ RT

Cross Reference Table				
Material	Standard	Country	Grade Belong to the Industry	
1.7362+l	EN	European Union	Steel and Tube	
1.7362+l	DIN	Germany	Steel	
1.7362+I	DIN	Germany	Steel	
X12CrMo5	DIN	Germany	Steel	
X11CrMo5TA	ISO	International	Steel	
X11CrMo5TN+TT	ISO	International	Steel and Tube	
X12CrMo5	EN	European Union	Steel	

Further any inquiry to discuss with Gravity Cast Pvt. Ltd. – Gravity Group of Companies team member Call on +918469160029, or email marketing@gravitycastindia.com

All information in our data sheets and website is indicative only and is not intended to be a substitute for the full specification from which it is extracted. It is intended to provide typical values to allow comparison between metal alloy option rather than a definitive statement of mechanical performance or suitability for a particular application as these will vary with temperature, product type and product application. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of business.