

Material - JIS SCPL 21

Standard Specification for Low Alloy Steel Castings for Low Temperature and High Pressure Service

Group - Ferrous Mild Steel Alloys

Sub Group - JIS SCPL 21 Low Alloy Steel Castings for Low Temperature and High Pressure Service Application - Intended for Valve, Pump, General Engineering, Automotive and Other Industries Grade Belongs to the Industry - Casting

Chemical Composition			Heat Treatment	
Carbon	C %	0.250 max.		
Silicon	Si %	0.600 max.		
Manganese	Mn %	0.500 - 0.800		
Phosphorus	Р%	0.040 max.	Normalising + Tempering or Hardening + Tempering	lardening + Tempering
Sulphur	S %	0.040 max.		
Chromium	Cr %	0.350 max.		
Nickel	Ni %	2.000 - 3.000		
Copper	Cu %	0.500 max.		
Iron	Fe %	Balance	Mechanical Properties	
-	-	-	Tensile Strength in Mpa	480 min.
-	-	-	Yield Strength in Mpa	275 min.
	-	-	Elongation in %	21 min.
	-	-	Reduction of Area in %	35 min.
-	-	-	Hardne <mark>ss in BHN</mark>	-
-	-	-	Impa <mark>ct in Joule</mark>	-

Cross Reference Table				
Material	Standard	Country	Grade Belong to the Industry	
SA-352 LC2	ASME	USA	Casting	
1.5635	DIN	Germany	Steel	
G22Ni10	UNI	Italy	Casting	
G9Ni10	AFNOR NF	France	Casting	
J22500	UNS	USA	Casting	
F.8373	UNE	Spain	Casting	
A352 LC2	ASTM	USA	Casting	

Further any inquiry to discuss with Gravity Cast Pvt. Ltd. – Gravity Group of Companies team member Call on +918469160029, or email marketing@gravitycastindia.com

All information in our data sheets and website is indicative only and is not intended to be a substitute for the full specification from which it is extracted. It is intended to provide typical values to allow comparison between metal alloy option rather than a definitive statement of mechanical performance or suitability for a particular application as these will vary with temperature, product type and product application. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of business.

ONE STOP SOLUTION FOR METAL PARTS