

Material - JIS SCS 23

Standard Specification for Austenitic Stainless Steel Castings for General Application

Group - Ferrous Stainless Steel Alloys

Sub Group - JIS SCS 23 Austenitic Stainless Steel Castings for General Application

Application - Intended for Valve, Pump, General Engineering, Automotive and Other Industries Grade Belongs to the Industry - Centrifugal Cast, Steel, Pipes

Chemical Composition			Heat Treatment	
Carbon	C %	0.070 max.	Solution Annealing	
Silicon	Si %	2.000 max.		
Manganese	Mn %	2.000 max.		
Phosphorus	Р%	0.040 max.		
Sulphur	S %	0.040 max.		
Chromium	Cr %	19.000 - 22.000		
Nickel	Ni %	27.500 - 30.000		
Molybdenum	Mo %	2.000 - 3.000		
Copper	Cu %	3.000 - 4.000	Mechanical Properties	
Iron	Fe %	Balance	Tensile Strength in Mpa	390 min
-	-	-	Yield Strength in Mpa	165 min.
-	-	-	Elongation in %	30 min.
-	-	-	Reduction of Area in %	-
-	-	-	Hardness in HB	183 max.
-	-	-	Impac <mark>t in Joule</mark>	-

Cross Reference Table				
Material	Standard	Country	Grade Belong to the Industry	
1.4500 DIN	DIN	Germany	Casting	
SA-351 CN7M	ASME	USA	Casting	
G X 5 NiCrCuMo 29-21	UNI	Italy	Casting	
F.8417	UNE	Spain	Casting	
A744 CN7M	ASTM	USA	Casting	
A743 CN7M	ASTM	USA	Casting	
A351 CN7M	ASTM	USA	Casting	

Further any inquiry to discuss with Gravity Cast Pvt. Ltd. – Gravity Group of Companies team member Call on +918469160029, or email marketing@gravitycastindia.com

All information in our data sheets and website is indicative only and is not intended to be a substitute for the full specification from which it is extracted. It is intended to provide typical values to allow comparison between metal alloy option rather than a definitive statement of mechanical performance or suitability for a particular application as these will vary with temperature, product type and product application. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of business.

ONE STOP SOLUTION FOR METAL PARTS