



## Material - JIS SCW 520-CF

## **Standard Specification for Steel Castings for Pressure Purposes**

**Group - Ferrous Mild Steel Alloys** 

Sub Group - JIS SCW 520-CF Steel Castings for Pressure Purposes

Application - Intended for Valve, Pump, General Engineering, Automotive and Other Industries

**Grade Belongs to the Industry - Casting** 

Chemical Composition			Heat Treatment	
Carbon	C %	0.200 max.		
Silicon	Si %	0.800 max.	Normalizing or Quenching or Solution Annealing	
Manganese	Mn %	1.500 max.		
Phosphorus	P %	0.040 max.		
Sulphur	S %	0.040 max.		
Chromium	Cr %	0.500 max.		
Nickel	Ni %	0.500 max.		
Iron	Fe %	Balance		•
-	-	-	Mechanical Properties	
-	-		Tensile Strength in Mpa	520 min.
-	-	-	Yield Strength in Mpa	355 min.
-	-	-	Elongation in %	18 min.
-	-	-	Reduction of Area in %	-
-	-	-	Hardness in HB	-
-	-	-	Impac <mark>t in Joule</mark>	27 J @ RT

Cross Reference Table				
Material	Standard	Country	Grade Belong to the Industry	
EN 10213 G20Mn5	BS	British	Plate, Tubes and Forging	
1.6220	ISO	International	Casting	
G20Mn5	ISO	International	Casting	
GS-20 Mn 5	DIN	Germany	Casting	
SCC 3	JIS	Japan	Casting	
SCPH 11-CF	JIS	Japan	Casting	
SCW 550	JIS	Japan	Casting	

Further any inquiry to discuss with Gravity Cast Pvt. Ltd. – Gravity Group of Companies team member Call on +918469160029, or email marketing@gravitycastindia.com

All information in our data sheets and website is indicative only and is not intended to be a substitute for the full specification from which it is extracted. It is intended to provide typical values to allow comparison between metal alloy option rather than a definitive statement of mechanical performance or suitability for a particular application as these will vary with temperature, product type and product application. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of business.