



Material - JIS SKS 43

Standard Specification for Steel Castings for General Engineering Purposes

Group - Ferrous Mild Steel Alloys

Sub Group - JIS SKS 43 Steel Castings for General Engineering Purposes

Application - Intended for Valve, Pump, General Engineering, Automotive and Other Industries

Grade Belongs to the Industry - Casting

Chemical Composition			Heat Treatment	
Carbon	C %	1.000 - 1.100		
Silicon	Si %	0.100 - 0.300	As Cast or Annealing or Normalizing or Hardening and Tempering	
Manganese	Mn %	0.100 - 0.400		alizing or Hardoning and
Phosphorus	P %	0.030 max.		ŭ
Sulphur	S %	0.030 max.		IIIR
Chromium	Cr %	0.200 max.		
Copper	Cu %	0.250 max.		
Nickel	Ni %	0.250 max.		-
Vanadium	V %	0.100 - 0.200	Mechanical Properties	
Iron	Fe %	Balance	Tensile Strength in Mpa	-
-	-	-	Yield Strength in Mpa	-
-	-	-	Elongation in %	-
-	-	-	Reduction of Area in %	-
-	-	-	Hardness in BHN	212 max.
-	-	-	Impac <mark>t in Joule</mark>	-

Cross Reference Table				
Material	Standard	Country	Grade Belong to the Industry	
BW2	BS	British	Casting	
BW3	BS	British	Casting	
BW4	BS	British	Casting	
1.2833	DIN	Germany	Casting	
5145	SAE	USA	Casting	
5145	AISI	USA	Casting	
A 29 5145	ASTM	USA	Casting	

Further any inquiry to discuss with Gravity Cast Pvt. Ltd. – Gravity Group of Companies team member Call on +918469160029, or email marketing@gravitycastindia.com

All information in our data sheets and website is indicative only and is not intended to be a substitute for the full specification from which it is extracted. It is intended to provide typical values to allow comparison between metal alloy option rather than a definitive statement of mechanical performance or suitability for a particular application as these will vary with temperature, product type and product application. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of business.