GRAVITY CAST PVT. LTD.
GRAVITY GROUP OF COMPANIES

Material - KS D 3698 STS410

Standard Specification for Cold-Rolled Stainless Steel Sheet and Strip

Group - Ferrous Stainless Steel Alloys

Sub Group - KS D 3698 STS410 Cold-Rolled Stainless Steel Sheet and Strip

Application - Intended for Valve, Pump, General Engineering, Automotive and Other Industries

Grade Belongs to the Industry - Sheet and Strip

Chemical Composition		
Carbon	C %	0.150 max.
Silicon	Si %	1.000 max.
Manganese	Mn %	1.000 max.
Phosphorus	P %	0.040 max.
Sulphur	S %	0.030 max.
Chromium	Cr %	11.500 - 13.500
Nickel	Ni %	0.600 max.
Iron	Fe %	Balance
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-

Heat Treatment
As-Raw or Annealing or Quenching + Tempering

Mechanical Properties	
Tensile Strength in Mpa	440 min.
Yield Strength in Mpa	205 min.
Elongation in %	20 min.
Reduction of Area in %	-
Hardness in HB	201 max.
Impact in Joule	-

www.gravitycastindia.com

Cross Reference Table			
Material	**Standard**	**Country**	**Grade Belong to the Industry**
D 3703 STS 410	KS	Korea	Steel and Wire
D 3702 STS 410	KS	Korea	Steel and Wire Rods
G 4308 SUS 410	JIS	Japan	Steel and Wire Rods
G 4312 SUS 410	JIS	Japan	Plate and Sheet
G 4311 SUS 410	JIS	Japan	Steel and Bars
SA-240 Type 410	ASME	USA	Plate, Sheet and Strip
A 176 Type 410	ASTM	USA	Plate, Sheet and Strip

Further any inquiry to discuss with Gravity Cast Pvt. Ltd. – Gravity Group of Companies team member Call on +918469160029, or email marketing@gravitycastindia.com

All information in our data sheets and website is indicative only and is not intended to be a substitute for the full specification from which it is extracted. It is intended to provide typical values to allow comparison between metal alloy option rather than a definitive statement of mechanical performance or suitability for a particular application as these will vary with temperature, product type and product application. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of business.