



Material - SAE 1060

Standard Specification For Carbon Steel Compositions For Forging To Hot-Rolled And Cold-Finished Steel

Group - Ferrous Mild Steel Alloys

Sub Group - SAE 1060 Carbon Steel Compositions For Forging To Hot-Rolled Steel
Application - Intended for Valve, Pump, General Engineering, Automotive and Other Industries
Grade Belongs to the Industry - Steel

Chemical Composition			Heat Treatment	
Carbon	C %	0.550 - 0.650		
Manganese	Mn %	0.600 - 0.900	As Raw or Annealing or Normalizing or Hardening and Tempering	
Phosphorus	P %	0.030 max.		olizing or Hardoning and
Sulphur	S %	0.035 max.		
Boron	В %	0.0005 - 0.003		ng
Copper	Cu %	0.200 min.		
Chromium	Cr %	0.150 max.		
Molybdenum	Mo %	0.060 max.		
Nickel	Ni %	0.200 max.	Mechanical Properties	
Lead	Pb %	0.150 - 0.350	Tensile Strength in Mpa	620 - 680
Iron	Fe %	Balance	Yield Strength in Mpa	370 min.
-	-	-	Elongation in %	10 min.
-	-	-	Reduction of Area in %	30 - 45
-	-	-	Hardness in HB	183 - 201
-	-	-	Impact in Joule	-

Cross Reference Table					
Material	Standard	Country Grade Belong to the Industry			
G10600	UNS	USA	Bars, Wire Rods, Plates, Strip, Sheets and Tubing		
1060	AISI	USA	Steel and Tubing		
A 1040 1060	ASTM	USA	Steel		
A 29 1060	ASTM	USA	Stee and Bar		
A 510 1060	ASTM	USA	Wire Rod, Round Rod and Steel		
A 513 Grade 1060	ASTM	USA	Steel and Tubing		
A 576 10L60	ASTM	USA	Bar		

Further any inquiry to discuss with Gravity Cast Pvt. Ltd. – Gravity Group of Companies team member Call on +918469160029, or email marketing@gravitycastindia.com

All information in our data sheets and website is indicative only and is not intended to be a substitute for the full specification from which it is extracted. It is intended to provide typical values to allow comparison between metal alloy option rather than a definitive statement of mechanical performance or suitability for a particular application as these will vary with temperature, product type and product application. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of business.