

Material - SAE J403 I J1397 UNS G10160 - Cold Drawn

Standard Specification For Carbon Steel Compositions For Forging To Hot-Rolled And Cold-Finished Bars, To Wire Rods, Plates, Strip, Sheets, Tubing

Group - Ferrous Stainless Steel Alloys

Sub Group - SAE J403 I J1397 UNS G10160 - Cold Drawn Carbon Steel Compositions For Forging To Hot-Rolled And Cold-Finished Bars, Wire Rods, Plates, Strip, Sheets and Tubing

Application - Intended for Valve, Pump, General Engineering, Automotive and Other Industries Grade Belongs to the Industry - Bars, Wire Rods, Plates, Strip, Sheets and Tubing

Chemical Composition			Heat Treatment	
Carbon	C %	0.130 - 0.180		
Manganese	Mn %	0.600 - 0.900		
Phosphorus	P %	0.030 max.	As Raw or Annealing or Normalizing or Hardening and	
Sulphur	S %	0.050 max.		
Iron	Fe %	Balance	Tempering	ııg
-	-	-		
-	-	-		
-	-	-		
-	-	-	Mechanical Properties	
-	-	-	Tensile Strength in Mpa	420 min.
-	-	-	Yield Strength in Mpa	350 min.
-	-	-	Elongation in %	18 min.
-	-	-	Reduction of Area in %	40 min.
-	-	-	Hardness in HB	121 max.
-	-	-	Impact in Joule	-

Cross Reference Table					
Material	Standard	Country	Grade Belong to the Industry		
1016	SAE	USA	Bars, Wire Rods and Tubing		
1016	AISI	USA	Tubing		
A 1040 1016	ASTM	USA	Steel		
A 108 Grade 1016	ASTM	USA	Steel and Bar		
A 29 1016	ASTM	USA	Steel and Bar		
A 510 1016	ASTM	USA	Wire Rods		
A 512 Grade 1016	ASTM	USA	Tubing		

Further any inquiry to discuss with Gravity Cast Pvt. Ltd. – Gravity Group of Companies team member Call on +918469160029, or email marketing@gravitycastindia.com

All information in our data sheets and website is indicative only and is not intended to be a substitute for the full specification from which it is extracted. It is intended to provide typical values to allow comparison between metal alloy option rather than a definitive statement of mechanical performance or suitability for a particular application as these will vary with temperature, product type and product application. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of business.