

Material - SAE J403 I SAE J1397 UNS G10200 - Cold Drawn

Standard Specification For Carbon Steel Compositions For Forging To Hot-Rolled And Cold-Finished Bars, To Wire Rods, Plates, Strip, Sheets and Tubing

Group - Ferrous Mild Steel Alloys

Sub Group - SAE J403 I SAE J1397 UNS G10200 - Cold Drawn Carbon Steel Compositions For Forging To Hot-Rolled And Cold-Finished Bars, Wire Rods, Plates, Strip, Sheets and Tubing

Application - Intended for Valve, Pump, General Engineering, Automotive and Other Industries Grade Belongs to the Industry - Bars, Wire Rods, Plates, Strip, Sheets and Tubing

Chemical Composition			Heat Treatment	
Carbon	C %	0.180 - 0.230		
Manganese	Mn %	0.300 - 0.600	As Raw or Annealing or Normalizing or Hardening and	
Phosphorus	P %	0.030 max.		olizing or Hardoning and
Sulphur	S %	0.050 max.	Tempering	
Iron	Fe %	Balance	rempering	iig
-	-	-		
-	-	-		
-	-	-		
-	-	-	Mechanical Properties	
-	-	-	Tensile Strength in Mpa	420 min.
-	-	-	Yield Strength in Mpa	350 min.
-	-	-	Elongation in %	15 min.
-	-	-	Reduction of Area in %	40 min.
-	-	-	Hardness in HB	121 max.
-	-	-	Impact in Joule	-
- - - - - - - -	-		Tensile Strength in Mpa Yield Strength in Mpa Elongation in % Reduction of Area in % Hardness in HB	420 min. 350 min. 15 min. 40 min.

Cross Reference Table					
Material	Standard	Country	Grade Belong to the Industry		
1020	SAE	USA	Sheet, Strip and Plate		
1020	AISI	USA	Sheet, Strip and Plate		
A 1040 1020	ASTM	USA	Steel		
A 108 Grade 1020	ASTM	USA	Steel and Bar		
A 29 1020	ASTM	USA	Steel and Bar		
A 29 M1020	ASTM	USA	Steel and Bar		
A 510 1020	ASTM	USA	Wire Rod and Round Wire		

Further any inquiry to discuss with Gravity Cast Pvt. Ltd. – Gravity Group of Companies team member Call on +918469160029, or email marketing@gravitycastindia.com

All information in our data sheets and website is indicative only and is not intended to be a substitute for the full specification from which it is extracted. It is intended to provide typical values to allow comparison between metal alloy option rather than a definitive statement of mechanical performance or suitability for a particular application as these will vary with temperature, product type and product application. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of business.