

Material - SAE J403 I SAE J1397 UNS G10400 - Cold Drawn

Standard Specification For Carbon Steel Compositions For Forging To Hot-Rolled And Cold-Finished Bars, To Wire Rods, Plates, Strip, Sheets and Tubing

Group - Ferrous Mild Steel Alloys

Sub Group - SAE J403 I SAE J1397 UNS G10400 - Cold Drawn Carbon Steel Compositions For Forging To Hot-Rolled And Cold-Finished Bars, Wire Rods, Plates, Strip, Sheets and Tubing

Application - Intended for Valve, Pump, General Engineering, Automotive and Other Industries Grade Belongs to the Industry - Bars, Wire Rods, Plates, Strip, Sheets and Tubing

Chemical Composition			Heat Treatment	
Carbon	C %	0.370 - 0.440		
Manganese	Mn %	0.600 - 0.900	As Raw or Annealing or Normalizing or Hardening and Tempering	
Phosphorus	Р%	0.030 max.		lizing or Hardoning and
Sulphur	S %	0.050 max.		-
Iron	Fe %	Balance		ıg
-	-	-		
-	-	-		
-	-	-		
-		-	Mechanical Properties	
-	-	-	Tensile Strength in Mpa	590 min.
-	-	-	Yield Strength in Mpa	490 min.
-	-	-	Elongation in %	12 min.
-	-	-	Reduction of Area in %	35 min.
-	-	-	Hardn <mark>ess in HB</mark>	170 max.
-	-		Impact in Joule	-

Cross Reference Table				
Material	Standard	Country	Grade Belong to the Industry	
1040	SAE	USA	Steel	
1040	AISI	USA	Tubing	
A 1040 1040	ASTM	USA	Steel	
A 108 Grade 1040	ASTM	USA	Bar	
A 29 1040	ASTM	USA	Steel	
A 513 Grade 1040	ASTM	USA	Tubing	
A 510 1040	ASTM	USA	Wire Rod and Round Wire	

Further any inquiry to discuss with Gravity Cast Pvt. Ltd. – Gravity Group of Companies team member Call on +918469160029, or email marketing@gravitycastindia.com

All information in our data sheets and website is indicative only and is not intended to be a substitute for the full specification from which it is extracted. It is intended to provide typical values to allow comparison between metal alloy option rather than a definitive statement of mechanical performance or suitability for a particular application as these will vary with temperature, product type and product application. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of business.