

## Material - SAE J403 I SAE J1397 UNS G15520 - Cold Drawn

Standard Specification For Carbon Steel Compositions For Forging To Hot-Rolled And Cold-Finished Bars, To Wire Rods, Plates, Strip, Sheets and Tubing

**Group - Ferrous Mild Steel Alloys** 

Sub Group - SAE J403 I SAE J1397 UNS G15520 - Cold Drawn Carbon Steel Compositions For Forging To Hot-Rolled And Cold-Finished Bars, Wire Rods, Plates, Strip, Sheets and Tubing

Application - Intended for Valve, Pump, General Engineering, Automotive and Other Industries Grade Belongs to the Industry - Bars, Wire Rods, Plates, Strip, Sheets and Tubing

Chemical Composition			Heat Treatment	
Carbon	C %	0.470 - 0.550		
Manganese	Mn %	1.200 - 1.500	As Raw or Annealing or Normalizing or Hardening and Tempering	
Phosphorus	P %	0.030 max.		
Sulphur	S %	0.050 max.		
Iron	Fe %	Balance		
-	-	-		
-	-	-		
-	-	-		
-	7	-	Mechanical Pro	perties
-	-	-	Tensile Strength in Mpa	680 min.
-	-	-	Yield Strength in Mpa	570 min.
-	-	-	Elongation in %	10 min.
-	-	-	Reduction of Area in %	40 min.
-	-	-	Hardness in BHN	193 max.
-	-	-	Impac <mark>t in Joule</mark>	-

Cross Reference Table					
Material	Standard	Country Grade Belong to the Industry			
1552	SAE	USA	Bars, Wire Rods, Plates, Strip, Sheets and Tubing		
1552	AISI	USA	Steel and Bar		
A 29 1552	ASTM	USA	Steel and Bar		
A 510 1552	ASTM	USA	Wire Rod, Round Wire and Steel		
A 830 1552	ASTM	USA	Plate and Steel		
A 830 G15520	ASTM	USA	Plate and Steel		
A 866 1552	ASTM	USA	Steel		

Further any inquiry to discuss with Gravity Cast Pvt. Ltd. – Gravity Group of Companies team member Call on +918469160029, or email marketing@gravitycastindia.com

All information in our data sheets and website is indicative only and is not intended to be a substitute for the full specification from which it is extracted. It is intended to provide typical values to allow comparison between metal alloy option rather than a definitive statement of mechanical performance or suitability for a particular application as these will vary with temperature, product type and product application. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of business.