



Material - UNS J12524

Standard Specification for Steel Alloy Casting

Group - Ferrous Mild Steel Alloys
Sub Group - UNS J12524 Steel Alloy Casting
Application - Intended for Valve, Pump, General Engineering, A

Application - Intended for Valve, Pump, General Engineering, Automotive and Other Industries Grade Belongs to the Industry - Casting

Chemical Composition			Heat Treatment	
Carbon	C %	0.250 max.		
Silicon	Si %	0.600 max.	Normalising or Annealing or Hardening + Tempering	
Manganese	Mn %	0.500 - 0.800		
Phosphorus	P %	0.040 max.		
Sulphur	S %	0.045 max.		
Molybdenum	Mo %	0.450 - 0.650		
Nickel	Ni %	0.500 max.		
Tungsten	W %	0.100 max.		
Copper	Cu %	0.500 max.	Mechanical Properties	
Iron	Fe %	Balance	Tensile Strength in Mpa	450 - 620
-	-	-	Yield Strength in Mpa	240 min.
-	-	-	Elongation in %	24 min.
-	-	-	Reduction of Area in %	35 min.
-	-	-	Hardness in BHN	-
-	-	-	Impac <mark>t in Joule</mark>	-

Cross Reference Table				
Material	Standard	Country	Grade Belong to the Industry	
SA217 WC1	ASME	USA	Casting	
G20 Mo 5	EN	European Union	Casting	
SCPH 11	JIS	Japan	Casting	
A352 LC1	ASTM	USA	Casting	
G 20 MO5	DIN	Germany	Casting	
G 20 MO5	UNI	Italy	Casting	
A217 Grade WC1	ASTM	USA	Casting	

Further any inquiry to discuss with Gravity Cast Pvt. Ltd. – Gravity Group of Companies team member Call on +918469160029, or email marketing@gravitycastindia.com

All information in our data sheets and website is indicative only and is not intended to be a substitute for the full specification from which it is extracted. It is intended to provide typical values to allow comparison between metal alloy option rather than a definitive statement of mechanical performance or suitability for a particular application as these will vary with temperature, product type and product application. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of business.