



## Material - ASME SA-312 S35045

Standard Specification for Seamless and Heavily Cold Worked Austenitic Stainless Steel Pipes

**Group - Non-Ferrous Nickel Alloys** 

Sub Group - ASME SA-312 S35045 Seamless and Heavily Cold Worked Austenitic Stainless Steel Pipes Application - Intended for Valve, Pump, General Engineering, Automotive and other Industries Grade Belongs to the Industry - Pipe

Chemical Composition			Heat Treatment	
Carbon	C %	0.060 - 0.100		
Silicon	Si %	1.000 max.		
Manganese	Mn %	1.500 max.		
Chromium	Cr %	25.000 - 29.000	As-Cast or Annealing or Age Hardning	
Sulphur	S %	0.015 max.		
Copper	Cu %	0.750 max.		
Aluminium	Al %	0.150 - 0.600		
Titanium	Ti %	0.150 - 0.600		
Nickel	Ni %	32.000 - 37.000	Mechanical Properties	
Iron	Fe %	Balance	Tensile Strength in Mpa	485 min.
-	-	-	Yield Strength in Mpa	170 min.
-	-	-	Elongation in %	25 min.
-	-		Reduction of Area in %	-
-	-		Hardness in BHN	-
-	-	-	Impact in Joule	-

Cross Reference Table				
Material	Standard	Country Grade Belong to the Industry		
Incoloy Alloy 803	Gravity	India	Pipe, Tube, Sheet, Strip, Plate, Hexagon and Wire	
A 312 S35045	ASTM	USA	Pipe	
-	-	-	-	
-	-	-	-	
-	-	-	-	
-	-	-	-	
-	-	-	-	

Further any inquiry to discuss with Gravity Cast Pvt. Ltd. – Gravity Group of Companies team member Call on +918469160029, or email marketing@gravitycastindia.com

All information in our data sheets and website is indicative only and is not intended to be a substitute for the full specification from which it is extracted. It is intended to provide typical values to allow comparison between metal alloy option rather than a definitive statement of mechanical performance or suitability for a particular application as these will vary with temperature, product type and product application. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of business.