



Material - ASME SB-163 N06600

Standard Specification for Seamless Nickel and Nickel Alloy Condenser and Heat-Exchanger Tubes

Group - Non-Ferrous Nickel Alloys

Sub Group - ASME SB-163 N06600 Seamless Nickel and Nickel Alloy Condenser and Heat-Exchanger Tube Application - Intended for Valve, Pump, General Engineering, Automotive and other Industries Grade Belongs to the Industry - Tube

| Chemical Composition | | | Heat Treatment | |
|----------------------|------|-----------------|--------------------------------------|-----------|
| Carbon | C % | 0.150 max. | | |
| Silicon | Si % | 0.500 max. | | |
| Manganese | Mn % | 1.000 max. | | |
| Copper | Cu % | 0.500 max. | As-Cast or Annealing or Age Hardning | |
| Sulphur | S % | 0.015 max. | | |
| Chromium | Cr % | 14.000 - 17.000 | | |
| Iron | Fe % | 6.000 - 10.000 | | |
| Nickel | Ni % | 72.000 min. | | |
| - | - | - | Mechanical Properties | |
| - | - | - | Tensile Strength in Mpa | 552 - 758 |
| - | - | - | Yield Strength in Mpa | 241 - 448 |
| - | - | - | Elongation in % | 4 min. |
| - | - | - | Reduction of Area in % | - |
| - | - | - | Hardness in HRC | 19 - 98 |
| - | - | - | Impa <mark>ct in Joule</mark> | - |

| Cross Reference Table | | | | |
|-----------------------|----------|---------------|------------------------------|--|
| Material | Standard | Country | Grade Belong to the Industry | |
| B 163 N06600 | ASTM | USA | Tube | |
| B 166 N06600 | ASTM | USA | Rod, Bar and Wire | |
| B 167 N06600 | ASTM | USA | Pipe and Tube | |
| B 168 N06600 | ASTM | USA | Plate, Sheet and Strip | |
| B 472 N06600 | ASTM | USA | Bar | |
| NiCr15Fe8 | ISO | International | Plate, Sheet and Strip | |
| NW6600 | JIS | Japan | Plate, Sheet and Strip | |

Further any inquiry to discuss with Gravity Cast Pvt. Ltd. – Gravity Group of Companies team member Call on +918469160029, or email marketing@gravitycastindia.com

All information in our data sheets and website is indicative only and is not intended to be a substitute for the full specification from which it is extracted. It is intended to provide typical values to allow comparison between metal alloy option rather than a definitive statement of mechanical performance or suitability for a particular application as these will vary with temperature, product type and product application. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of business.

ONE STOP SOLUTION FOR METAL PARTS