

## Material - ASME SB-619 N06985

## Standard Specification for Nickel and Nickel-Cobalt Alloy Pipe

Group - Non-Ferrous Nickel Alloys

Sub Group - ASME SB-619 N06985 Nickel and Nickel-Cobalt Alloy Pipe

Application - Intended for Valve, Pump, General Engineering, Automotive and other Industries

Grade Belongs to the Industry - Pipe

Chemical Composition			Heat Treatment	
Carbon	C %	0.015 max.		
Silicon	Si %	1.000 max.		
Manganese	Mn %	1.000 max.	As-Cast or Annealing or Age Hardning	
Chromium	Cr %	21.000 - 23.500		
Sulphur	S %	0.030 max.		
Molybdenum	Mo %	6.000 - 8.000		
Phosphorus	P %	0.040 max.		
Nb + Ta	Nb% + Ta%	0.500 max.		
Tungsten	W %	1.500 max.	Mechanical Properties	
Copper	Cu %	1.500 - 2.500	Tensile Strength in Mpa	621 min.
Cobalt	Co %	5.000 max.	Yield Strength in Mpa	241 min.
Iron	Fe %	18.000 - 21.000	Elongation in %	45 min.
Nickel	Ni %	Balance	Reduction of Area in %	-
-	-	-	Hardn <mark>ess in BH</mark> N	-
-	-	-	Impac <mark>t in Joule</mark>	-

Cross Reference Table				
Material	Standard	Country	Grade Belong to the Industry	
B 581 N06975	ASTM	USA	Rod	
B 582 N06985	ASTM	USA	Plate, Sheet and Strip	
B 622 N06985	ASTM	USA	Pipe and Tube	
B 626 N06985	ASTM	USA	Tube	
B 581 N06975	ASTM	USA	Rod	
SB-582 N06985	ASME	USA	Plate, Sheet and Strip	
B 619 N06975	ASTM	USA	Pipe	

## Further any inquiry to discuss with Gravity Cast Pvt. Ltd. – Gravity Group of Companies team member Call on +918469160029, or email marketing@gravitycastindia.com

All information in our data sheets and website is indicative only and is not intended to be a substitute for the full specification from which it is extracted. It is intended to provide typical values to allow comparison between metal alloy option rather than a definitive statement of mechanical performance or suitability for a particular application as these will vary with temperature, product type and product application. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of business.

## **ONE STOP SOLUTION FOR METAL PARTS**