

## Material - ASTM A 269 N08904

Standard Specification for Seamless Ferritic and Austenitic Alloy-Steel Boiler, Superheater, and Heat-Exchanger Tubes

**Group - Non-Ferrous Nickel Alloys** 

Sub Group - ASTM A 269 N08904 Seamless Ferritic and Austenitic Alloy-Steel Boiler, Superheater, and Heat-Exchanger Tubes

Application - Intended for Valve, Pump, General Engineering, Automotive and other Industries Grade Belongs to the Industry - Tube

Chemical Composition			Heat Treatment	
Carbon	C %	0.020 max.		
Silicon	Si %	1.000 max.		
Manganese	Mn %	2.000 max.		
Chromium	Cr %	19.000 - 23.000	As-Cast or Annealing or Age Hardning	or Age Hardning
Sulphur	S %	0.030 max.		
Molybdenum	Mo %	4.000 - 5.000		
Phosphorus	P %	0.040 max.		
Copper	Cu %	1.000 - 2.000		-
Nitrogen	N %	0.100 max.	Mechanical Properties	
Nickel	Ni %	23.000 - 28.000	Tensile Strength in Mpa	-
-	-	-	Yield Strength in Mpa	-
-	-	-	Elongation in %	-
-	-		Reduction of Area in %	
-	-	-	Hardness in HRC	90 max.
-	-	-	Impac <mark>t in Joule</mark>	-

Cross Reference Table					
Material	Standard	Country	Grade Belong to the Industry		
B 649 N08904	ASTM	USA	Bar and Wire		
A 182 F 904L	ASTM	USA	Pipe Flanges, Forged Fittings and Valves		
A 213 N08904	ASTM	USA	Tube		
A 249 N08904	ASTM	USA	Tube		
A 312 N08904	ASTM	USA	Pipe		
A 511 N08904	ASTM	USA	Bar		
A 965 N08904	ASTM	USA	Forging		

Further any inquiry to discuss with Gravity Cast Pvt. Ltd. – Gravity Group of Companies team member Call on +918469160029, or email marketing@gravitycastindia.com

All information in our data sheets and website is indicative only and is not intended to be a substitute for the full specification from which it is extracted. It is intended to provide typical values to allow comparison between metal alloy option rather than a definitive statement of mechanical performance or suitability for a particular application as these will vary with temperature, product type and product application. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of business.