



Material - ASTM B 472 N10675

Standard Specification for Nickel Alloy Billets and Bars for Reforging

Group - Non-Ferrous Nickel Alloys

Sub Group - ASTM B 472 N10675 Nickel Alloy Billets and Bars for Reforging

Application - Intended for Valve, Pump, General Engineering, Automotive and other Industries Grade Belongs to the Industry - Bar

| Chemical Composition | | | Chemical Composition | | |
|----------------------|------|-----------------|--------------------------------------|-----------|-------------|
| Carbon | C % | 0.010 max. | Tantalum | Ta % | 0.200 max. |
| Silicon | Si % | 0.100 max. | Zirconium | Zr % | 0.100 max. |
| Manganese | Mn % | 3.000 max. | Ni + Mo | Ni% + Mo% | 94.000 - |
| Copper | Cu % | 0.200 max. | Nickel | Ni % | 65.000 min. |
| Sulphur | S % | 0.010 max. | - | - | - |
| Chromium | Cr % | 1.000 - 3.000 | Heat Treatment | | |
| Phosphorus | P % | 0.030 max. | As-Cast or Annealing or Age Hardning | | |
| Molybdenum | Mo % | 27.000 - 32.000 | | | |
| Iron | Fe % | 1.000 - 3.000 | Mechanical Properties | | |
| Cobalt | Co % | 3.000 max. | Tensile Strength in Mpa | 760 |) min. |
| Tungsten | W % | 3.000 max. | Yield Strength in Mpa | 350 min. | |
| Vanadium | V % | 0.200 max. | Elongation in % | 40 min. | |
| Titanium | Ti % | 0.200 max. | Reduction of Area in % | - | |
| Tungsten | W % | 3.000 max. | Hardness in BHN | - | |
| Niobium | Nb % | 0.200 max. | Impact i <mark>n Joule</mark> | - | |

| Cross Reference Table | | | | | |
|-----------------------|----------|---------|------------------------------|--|--|
| Material | Standard | Country | Grade Belong to the Industry | | |
| B 333 N10675 | ASTM | USA | Plate, Sheet and Strip | | |
| B 335 N10675 | ASTM | USA | Rod | | |
| B 564 N10675 | ASTM | USA | Forging | | |
| B 619 N10675 | ASTM | USA | Pipe | | |
| B 622 N10675 | ASTM | USA | Pipe and Tube | | |
| B 626 N10675 | ASTM | USA | Tube | | |
| - | - | - | - | | |

Further any inquiry to discuss with Gravity Cast Pvt. Ltd. – Gravity Group of Companies team member Call on +918469160029, or email marketing@gravitycastindia.com

All information in our data sheets and website is indicative only and is not intended to be a substitute for the full specification from which it is extracted. It is intended to provide typical values to allow comparison between metal alloy option rather than a definitive statement of mechanical performance or suitability for a particular application as these will vary with temperature, product type and product application. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of business.

ONE STOP SOLUTION FOR METAL PARTS