



Material - ASTM B 582 N06985

Standard Specification for Nickel-Chromium-Iron-Molybdenum-Copper Alloy Plate, Sheet and Strip

Group - Non-Ferrous Nickel Alloys

Sub Group - ASTM B 582 N06985 Nickel-Chromium-Iron-Molybdenum-Copper Alloy Plate, Sheet and Strip Application - Intended for Valve, Pump, General Engineering, Automotive and other Industries Grade Belongs to the Industry - Plate, Sheet and Strip

Chemical Composition			Heat Treatment	
Carbon	C %	0.015 max.		
Silicon	Si %	1.000 max.		
Manganese	Mn %	1.000 max.		
Chromium	Cr %	21.000 - 23.500	As-Cast or Annealing	or Age Hardning
Sulphur	S %	0.030 max.		
Molybdenum	Mo %	6.000 - 8.000		
Phosphorus	Р%	0.040 max.		
Cobalt	Co %	5.000 max.		
Copper	Cu %	1.500 - 2.500	Mechanical Properties	
Tungsten	W %	1.500 max.	Tensile Strength in Mpa	586 min.
Nb + Ta	Nb% + Ta%	0.500 max.	Yield Strength in Mpa	207 min.
Iron	Fe %	18.000 - 21.000	Elongation in %	35 min.
Nickel	Ni %	Balance	Reduction of Area in %	-
-	-	-	Hardness in HRC	100 max.
-	-	-	Impa <mark>ct in Joule</mark>	-

Cross Reference Table				
Material	Standard	Country	Grade Belong to the Industry	
B 581 N06975	ASTM	USA	Rod	
B 619 N06985	ASTM	USA	Pipe	
B 622 N06985	ASTM	USA	Pipe and Tube	
B 626 N06985	ASTM	USA	Tube	
SB-581 N06985	ASME	USA	Rod	
SB-582 N06985	ASME	USA	Plate, Sheet and Strip	
SB-619 N06985	ASME	USA	Pipe	

Further any inquiry to discuss with Gravity Cast Pvt. Ltd. – Gravity Group of Companies team member Call on +918469160029, or email marketing@gravitycastindia.com

All information in our data sheets and website is indicative only and is not intended to be a substitute for the full specification from which it is extracted. It is intended to provide typical values to allow comparison between metal alloy option rather than a definitive statement of mechanical performance or suitability for a particular application as these will vary with temperature, product type and product application. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of business.

ONE STOP SOLUTION FOR METAL PARTS