

Material - ASTM B 622 N10629

Standard Specification for Seamless Nickel and Nickel-Cobalt Alloy Pipe and Tube Group - Non-Ferrous Nickel Alloys

Sub Group - ASTM B 622 N10629 Seamless Nickel and Nickel-Cobalt Alloy Pipe and Tube Application - Intended for Valve, Pump, General Engineering, Automotive and other Industries Grade Belongs to the Industry - Pipe and Tube

| Chemical Composition | | | Heat Treatment | |
|----------------------|------|-----------------|--------------------------------------|----------------|
| Carbon | C % | 0.010 max. | | |
| Silicon | Si % | 0.050 max. | | |
| Manganese | Mn % | 1.500 max. | As-Cast or Annealing or Age Hardning | |
| Copper | Cu % | 0.500 max. | | r Age Hardning |
| Sulphur | S % | 0.010 max. | | |
| Chromium | Cr % | 0.500 - 1.500 | | |
| Phosphorus | P % | 0.040 max. | | |
| Molybdenum | Mo % | 26.000 - 30.000 | | |
| Aluminium | AI % | 0.100 - 0.500 | Mechanical Properties | |
| Cobalt | Со % | 2.500 max. | Tensile Strength in Mpa | 760 min. |
| Iron | Fe % | 1.000 - 6.000 | Yield Strength in Mpa | 350 min. |
| Nickel | Ni % | Balance | Elongation in % | 40 min. |
| - | - | - | Reduction of Area in % | - |
| - | - | - | Hardness in BHN | - |
| - | - | - | Impac <mark>t in Joule</mark> | - |

| Cross Reference Table | | | | |
|-----------------------|----------|---------|------------------------------|--|
| Material | Standard | Country | Grade Belong to the Industry | |
| B 333 N10629 | ASTM | USA | Plate, Sheet and Strip | |
| B 335 N10629 | ASTM | USA | Rod | |
| B 564 N10629 | ASTM | USA | Forging | |
| B 472 N10629 | ASTM | USA | Bar | |
| B 619 N10629 | ASTM | USA | Pipe | |
| B 626 N10629 | ASTM | USA | Tube | |
| - | - | - | - | |

Further any inquiry to discuss with Gravity Cast Pvt. Ltd. – Gravity Group of Companies team member Call on +918469160029, or email marketing@gravitycastindia.com

All information in our data sheets and website is indicative only and is not intended to be a substitute for the full specification from which it is extracted. It is intended to provide typical values to allow comparison between metal alloy option rather than a definitive statement of mechanical performance or suitability for a particular application as these will vary with temperature, product type and product application. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of business.

ONE STOP SOLUTION FOR METAL PARTS