

## Material - ASTM B 674 N08925

Standard Specification for Nickel-Iron-Chromium-Molybdenum and Iron-Nickel-Chromium-Molybdenum-Copper Tube

## **Group - Non-Ferrous Nickel Alloys**

Sub Group - ASTM B 674 N08925 Nickel-Iron-Chromium-Molybdenum and Iron-Nickel-Chromium-Molybdenum-Copper Tube

Application - Intended for Valve, Pump, General Engineering, Automotive and other Industries Grade Belongs to the Industry - Tube

Chemical Composition			Heat Treatment	
Carbon	C %	0.020 max.		
Silicon	Si %	0.500 max.		
Manganese	Mn %	1.000 max.		
Chromium	Cr %	19.000 - 21.000	As-Cast or Annealing or Age Hardning	
Sulphur	S %	0.030 max.		
Molybdenum	Mo %	6.000 - 7.000		
Phosphorus	P %	0.045 max.		
Copper	Cu %	0.800 - 1.500		
Nitrogen	N %	0.100 - 0.200	Mechanical Properties	
Nickel	Ni %	24.000 - 26.000	Tensile Strength in Mpa	600 min.
Iron	Fe %	Balance	Yield Strength in Mpa	295 min.
-	-	-	Elongation in %	40 min.
	-	-	Reduction of Area in %	-
-	-	-	Hardne <mark>ss in BHN</mark>	-
-	-	-	Impac <mark>t in Joule</mark>	-
		-		

Cross Reference Table				
Material	Standard	Country Grade Belong to the Industry		
B 649 N08925	ASTM	USA	Bar and Wire	
A 182 F1925	ASTM	USA	Pipe Flanges, Forged Fittings and Valve	
B 625 N08925	ASTM	USA	Plate, Sheet and Strip	
B 673 N08925	ASTM	USA	Pipe	
B 677 N08925	ASTM	USA	Pipe and Tube	
SB-625 N08925	ASME	USA	Plate, Sheet and Strip	
SB-649 N08925	ASME	USA	Bar and Wire	

## Further any inquiry to discuss with Gravity Cast Pvt. Ltd. – Gravity Group of Companies team member Call on +918469160029, or email marketing@gravitycastindia.com

All information in our data sheets and website is indicative only and is not intended to be a substitute for the full specification from which it is extracted. It is intended to provide typical values to allow comparison between metal alloy option rather than a definitive statement of mechanical performance or suitability for a particular application as these will vary with temperature, product type and product application. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of business.

## **ONE STOP SOLUTION FOR METAL PARTS**