

Material - ASTM B 983 N07725 Type 2

Standard Specification for Precipitation Hardened or Cold Worked, Seamless Nickel Alloy Pipe and Tube

Group - Non-Ferrous Nickel Alloys

Sub Group - ASTM B 983 N07725 Type 2 Precipitation Hardened or Cold Worked, Seamless Nickel Alloy Pipe and Tube

Application - Intended for Valve, Pump, General Engineering, Automotive and other Industries Grade Belongs to the Industry - Pipe and Tube

| Chemical Composition | | | Heat Treatment | |
|----------------------|------|-----------------|--------------------------------------|-----------------|
| Carbon | C % | 0.030 max. | | |
| Silicon | Si % | 0.200 max. | | |
| Manganese | Mn % | 0.350 max. | | |
| Chromium | Cr % | 19.000 - 22.500 | As-Cast or Annealing or Age Hardning | or Age Hardning |
| Sulphur | S % | 0.010 max. | | |
| Molybdenum | Mo % | 7.000 - 9.500 | | |
| Phosphorus | Р% | 0.015 max. | | |
| Niobium | Nb % | 2.750 - 4.000 | | |
| Titanium | Ti % | 1.000 - 1.700 | Mechanical Properties | |
| Aluminium | Al % | 0.350 max. | Tensile Strength in Mpa | 1035 min. |
| Nickel | Ni % | 55.000 - 59.000 | Yield Strength in Mpa | 827 min. |
| Iron | Fe % | Balance | Elongation in % | 20 min. |
| - | - | - | Reduction of Area in % | - |
| - | - | - | Hardness in HRC | - |
| - | - | - | Impact in Joule | - |

| Cross Reference Table | | | | | |
|-----------------------|----------|---------|--|--|--|
| Material | Standard | Country | Gr <mark>ade Belong</mark> to the Industry | | |
| B 805 N07725 | ASTM | USA | Bar and Wire | | |
| B 872 N07725 | ASTM | USA | Plate, Sheet and Strip | | |
| B 983 N07725 Type 1 | ASTM | USA | Pipe and Tube | | |
| B1007 N07725 Type 1 | ASTM | USA | Tube | | |
| B1007 N07725 Type 2 | ASTM | USA | Tube | | |
| B1007 N07725 Type 3 | ASTM | USA | Tube | | |
| N07725 | UNS | USA | Pipe and Tube | | |

Further any inquiry to discuss with Gravity Cast Pvt. Ltd. – Gravity Group of Companies team member Call on +918469160029, or email marketing@gravitycastindia.com

All information in our data sheets and website is indicative only and is not intended to be a substitute for the full specification from which it is extracted. It is intended to provide typical values to allow comparison between metal alloy option rather than a definitive statement of mechanical performance or suitability for a particular application as these will vary with temperature, product type and product application. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of business.

ONE STOP SOLUTION FOR METAL PARTS