

Material - ASTM B111 C61400

Standard Specification for Copper and Copper-Alloy Seamless Condenser Tubes and Group - Non-Ferrous Copper Alloy

Sub Group - ASTM B111 Copper and Copper-Alloy Seamless Condenser Tubes and Ferrule Stock Application - Intended for Valve, Pump, General Engineering, Automotive and Other Industries Grade Belongs to the Industry - Tubes

Chemical Composition			Heat Treatment	
Aluminium	Al %	6.000 - 8.000		
Iron	Fe %	1.500 - 3.500	As Drawn or Stress Relieving	
Manganese	Mn %	1.000 max.		
Phosphorus	Р%	0.015 max.		Relieving
Lead	Pb %	0.010 max.		
Zinc	Zn %	0.200 max.		
Cu + Ag	Cu% + Ag%	Balance		
-	-	-		
-	-	-	Mechanical Properties	
-	-	-	Tensile Strength in Mpa	480 min.
-	-	-	Yield Strength in Mpa	205 min.
-	-	-	Elongation in %	-
	-	-	Reduction of Area in %	-
-	-	-	Hardness in BHN	-
-	-	-	Impac <mark>t in Joule</mark>	-

Cross Reference Table				
Material	Standard	Country	Grade Belong to the Industry	
C61400	UNS	USA	Rod, Bar, Tube and Shapes	
B100 C61400	ASTM	USA	Plate and Sheet	
B169 C61400	ASTM	USA	Sheet, Strip and Bar	
B171 C61400	ASTM	USA	Plate and Sheet	
B315 C61400	ASTM	USA	Pipe and Tube	
CA614	SAE	USA	Casting	
SB-150 C61400	ASME	USA	Rod, Bar and Shapes	

Further any inquiry to discuss with Gravity Cast Pvt. Ltd. – Gravity Group of Companies team member Call on +918469160029, or email marketing@gravitycastindia.com

All information in our data sheets and website is indicative only and is not intended to be a substitute for the full specification from which it is extracted. It is intended to provide typical values to allow comparison between metal alloy option rather than a definitive statement of mechanical performance or suitability for a particular application as these will vary with temperature, product type and product application. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of business.

ONE STOP SOLUTION FOR METAL PARTS