

## Material - ASTM B135 C37000

## Standard Specification for Seamless Brass Tube

Group - Non-Ferrous Copper Alloy

Sub Group - ASTM B135 Seamless Brass Tube

Application - Intended for Valve, Pump, General Engineering, Automotive and Other Industries

Grade Belongs to the Industry - Tube

Chemical Composition			Heat Treatment	
Iron	Fe %	0.150 max.		
Lead	Pb %	0.800 - 1.500		
Copper	Cu %	59.000 - 62.000		
Zinc	Zn %	Balance	Normalizing or Annealing or Tempering	g or Tempering
-	-	-		
-	-	-		
-	-	-		
-	-	-		
-	-	-	Mechanical Properties	
-	-	-	Tensile Strength in Mpa	372 min.
-	-	-	Yield Strength in Mpa	-
-	-	-	Elongation in %	-
-	-	-	Reduction of Area in %	-
-	-	-	Hardness in HRB	55 - 90
-	-	-	Impac <mark>t in Joule</mark>	-

Cross Reference Table				
Material	Standard	Country	Grade Belong to the Industry	
B283 C37000	ASTM	USA	Forging	
SB-283 C37000	ASME	USA	Forging	
C37000	UNS	USA	Rod, Bar and Shapes	
B124 C37000	ASTM	USA	Rod, Bar and Shapes	
-	-	-	-	
-	-	-	-	
-	-	-	-	

## Further any inquiry to discuss with Gravity Cast Pvt. Ltd. – Gravity Group of Companies team member Call on +918469160029, or email marketing@gravitycastindia.com

All information in our data sheets and website is indicative only and is not intended to be a substitute for the full specification from which it is extracted. It is intended to provide typical values to allow comparison between metal alloy option rather than a definitive statement of mechanical performance or suitability for a particular application as these will vary with temperature, product type and product application. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of business.

## ONE STOP SOLUTION FOR METAL PARTS