



Material - ASTM B150 C63000

Standard Specification for Aluminum Bronze Rod, Bar and Shapes

Group - Non-Ferrous Copper Alloy

Sub Group - ASTM B150 Aluminum Bronze Rod, Bar and Shapes

Application - Intended for Valve, Pump, General Engineering, Automotive and Other Industries

Grade Belongs to the Industry - Rod, Bar and Shape

| Chemical Composition | | | Heat Treatment | |
|----------------------|-----------|----------------|---------------------------------------|-----------|
| Aluminium | Al % | 9.000 - 11.000 | | |
| Iron | Fe % | 2.000 - 4.000 | | |
| Manganese | Mn % | 1.500 max. | Normalizing or Annealing or Tempering | |
| Ni + Co | Ni% + Co% | 4.000 - 5.500 | | |
| Silicon | Si % | 0.250 max. | | |
| Tin | Sn % | 0.200 max. | | |
| Zinc | Zn % | 0.300 max. | | |
| Cu + Ag | Cu% + Ag% | Balance | | |
| - | - | - | Mechanical Properties | |
| - | - | | Tensile Strength in Mpa | 550 - 760 |
| - | - | - | Yield Strength in Mpa | 275 - 475 |
| - | - | - | Elongation in % | 5 - 12 |
| - | - | - | Reduction of Area in % | - |
| - | - | - | Hardness in BHN | - |
| - | - | - | Impact in Joule | - |

| Cross Reference Table | | | | |
|-----------------------|----------|---------|------------------------------|--|
| Material | Standard | Country | Grade Belong to the Industry | |
| B124 C63000 | ASTM | USA | Rod, Bar and Shapes | |
| B171 C63000 | ASTM | USA | Plate and Sheet | |
| B283 C63000 | ASTM | USA | Forging | |
| SB-150 C63000 | ASME | USA | Rod, Bar and Shape | |
| SB-171 C63000 | ASME | USA | Plate and Sheet | |
| SB-283 C63000 | ASME | USA | Forging | |
| C63000 | UNS | USA | Rod, Bar and Shape | |

Further any inquiry to discuss with Gravity Cast Pvt. Ltd. – Gravity Group of Companies team member Call on +918469160029, or email marketing@gravitycastindia.com

All information in our data sheets and website is indicative only and is not intended to be a substitute for the full specification from which it is extracted. It is intended to provide typical values to allow comparison between metal alloy option rather than a definitive statement of mechanical performance or suitability for a particular application as these will vary with temperature, product type and product application. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of business.