

Material - ASTM B271 Leaded Red Brass UNS C83600

Standard Specification for Copper-Base Alloy Centrifugal Castings

Group - Non-Ferrous Copper Alloy

Sub Group - ASTM B271 Copper-Base Alloy Centrifugal Castings

Application - Intended for Valve, Pump, General Engineering, Automotive and Other Industries

Grade Belongs to the Industry - Rod, Bar, Tube and Shapes

Chemical Composition			Heat Treatment	
Tin	Sn %	4.000 - 6.000		
Lead	Pb %	4.000 - 6.000		
Zinc	Zn %	4.000 - 6.000		
Iron	Fe %	0.300 max.	As-Cast	
Ni + Co	Ni% + Co%	1.000 max.		
Aluminium	Al %	0.005 max.		
Silicon	Si %	0.005 max.		
Antimony	Sb %	0.250 max.		
Sulphur	S %	0.080 max.	Mechanical Properties	
Phosphorus	P %	0.050 max.	Tensile Strength in Mpa	207 min.
Copper	Cu %	84.000 - 86.000	Yield Strength in Mpa	97 min.
-	-	-	Elongation in %	20 min.
-	-		Reduction of Area in %	-
-	-	-	Hardness in BHN	-
-	-	-	Impac <mark>t in Joule</mark>	-

Cross Reference Table				
Material	Standard	Country	Grade Belong to the Industry	
B30 C83600	ASTM	USA	Ingot and Casting	
B62 C83600	ASTM	USA	Casting	
C83600	SAE	USA	Casting	
4855	SAE	USA	Casting	
CA836	SAE	USA	Casting	
SB-271 C83600	ASME	USA	Casting	
SB-505 C83600	ASME	USA	Casting	

Further any inquiry to discuss with Gravity Cast Pvt. Ltd. – Gravity Group of Companies team member Call on +918469160029, or email marketing@gravitycastindia.com

All information in our data sheets and website is indicative only and is not intended to be a substitute for the full specification from which it is extracted. It is intended to provide typical values to allow comparison between metal alloy option rather than a definitive statement of mechanical performance or suitability for a particular application as these will vary with temperature, product type and product application. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of business.