

Material - BS EN 1982 CuZn34Mn3Al2Fe1-C (CC764S)

Standard Specification for Copper and Copper Alloys - Ingot and Casting

Group - Non-Ferrous Copper Alloy

Sub Group - BS EN 1982 Standard Specification for Copper and Copper Alloys - Ingot and Casting Application - Intended for Valve, Pump, General Engineering, Automotive and Other Industries Grade Belongs to the Industry - Ingot and Casting

Chemical Composition			Heat Treatment	
Antimony	Sb %	0.005 max.		
Tin	Sn %	0.300 max.		
Silicon	Si %	0.100 max.	As-Cast	
Lead	Pb %	0.300 max.		
Phosphorus	Р%	0.030 max.		
Nickel	Ni %	3.000 max.		
Manganese	Mn %	1.000 - 4.000		
Iron	Fe %	0.500 - 2.500		
Aluminium	AI %	1.000 - 3.000	Mechanical Properties	
Copper	Cu %	55.000 - 66.000	Tensile Strength in Mpa	600 min.
Zinc	Zn %	Balance	Yield Strength in Mpa	250 min.
-	-	-	Elongation in %	15 min.
-	-	-	Reduction of Area in %	-
-	-	-	Hardness in HBW	140 min.
-	-	-	Impac <mark>t in Joule</mark>	-

Cross Reference Table				
Material	Standard	Country	Grade Belong to the Industry	
CB764S	AFNOR NF	France	Ingot and Casting	
CB764S	BDS	Bulgaria	Ingot and Casting	
CB764S	CSN	Czech Republic	Ingot and Casting	
CB764S	DIN	Germany	Ingot and Casting	
CuZn34Mn3Al2Fe1-B	UNI	Italy	Ingot and Casting	
CuZn34Mn3Al2Fe1-B	UNE	Spain	Ingot and Casting	
CuZn34Mn3Al2Fe1-B	MSZ	Hungary	Ingot and Casting	

Further any inquiry to discuss with Gravity Cast Pvt. Ltd. – Gravity Group of Companies team member Call on +918469160029, or email marketing@gravitycastindia.com

All information in our data sheets and website is indicative only and is not intended to be a substitute for the full specification from which it is extracted. It is intended to provide typical values to allow comparison between metal alloy option rather than a definitive statement of mechanical performance or suitability for a particular application as these will vary with temperature, product type and product application. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of business.

ONE STOP SOLUTION FOR METAL PARTS