

Material - BSI BS1400 SCB3 CuZn33Pb2

Standard Specification for Copper Alloy and High Conductivity Conductivity Copper Casting

Group - Non-Ferrous Copper Alloy

Sub Group - BSI BS1400 Copper Alloy and High Conductivity Conductivity Copper Casting Application - Intended for Valve, Pump, General Engineering, Automotive and Other Industries Grade Belongs to the Industry - Casting

Chemical Composition			Heat Treatment	
Tin	Sn %	1.500 max.		
Lead	Pb %	1.000 - 3.000		
Nickel	Ni %	1.000 max.		
Iron	Fe %	0.750 max.	As-Cast	
Aluminium	Al %	0.110 max.		
Manganese	Mn %	0.200 max.		
Silicon	Si %	0.050 max.		
Phosphorus	P %	0.050 max.		
Other	Ot%	1.000 max.	Mechanical Properties	
Copper	Cu %	63.000 - 67.000	Tensile Strength in Mpa	-
Zinc	Zn %	Balance	Yield Strength in Mpa	-
-	-	-	Elongation in %	-
-	-	-	Reduction of Area in %	-
-	-	-	Hardness in BHN	-
-	-	-	Impact in Joule	-

Cross Reference Table					
Material	Standard	Country	Grade Belong to the Industry		
854C	AS	Australia	Ingot and Casting		
C85400	AS	Australia Ingot and Casting			
CuZn33Pb2	ISO	International	Ingot and Casting		
-	-	-	-		
-	-	-	-		
-	-	-	-		
-	-	-	-		

Further any inquiry to discuss with Gravity Cast Pvt. Ltd. – Gravity Group of Companies team member Call on +918469160029, or email marketing@gravitycastindia.com

All information in our data sheets and website is indicative only and is not intended to be a substitute for the full specification from which it is extracted. It is intended to provide typical values to allow comparison between metal alloy option rather than a definitive statement of mechanical performance or suitability for a particular application as these will vary with temperature, product type and product application. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of business.