

Material - DIN CEN/TS 13388 CuNi18Zn27

Standard Specification for Copper and Copper Alloy

Group - Non-Ferrous Copper Alloy

Sub Group - DIN CEN/TS 13388 Copper and Copper Alloy

Application - Intended for Valve, Pump, General Engineering, Automotive and Other Industries Grade Belongs to the Industry - Plate, Sheet and Strip

Chemical Composition Heat Treatment 0.300 max. Iron Fe % 0.500 max. Manganese Mn % Ni % 17.000 - 19.000 Nickel Other 0.200 max. Normalizing or Annealing or Tempering Ot% 0.030 max. Lead Pb % 0.030 max. Tin Sn % 53.000 - 56.000 Copper Cu % Zinc Zn % Balance **Mechanical Properties** -_ _ Tensile Strength in Mpa 390 - 800 _ Yield Strength in Mpa 280 - 660 _ _ Elongation in % 2 - 40 _ _ _ **Reduction of Area in %** Hardness in HB _ _ 85 - 210 Impact in Joule _ -_ -

Cross Reference Table			
Material	Standard	Country	Grade Belong to the Industry
CuNi18Zn27	IS	India	Rod and Bar
CuNi18Zn27	ISO	International	Plate, Sheet and Strip
B122 C77000	ASTM	USA	Plate, Sheet, Strip and Rolled Bar
B151 C77000	ASTM	USA	Rod and Bar
B206 C77000	ASTM	USA	Wire
CuNi18Zn20	ISO	International	Plate, Sheet and Strip
CuNi18Zn27	AFNOR NF	France	Plate, Sheet and Strip

Further any inquiry to discuss with Gravity Cast Pvt. Ltd. – Gravity Group of Companies team member Call on +918469160029, or email marketing@gravitycastindia.com

All information in our data sheets and website is indicative only and is not intended to be a substitute for the full specification from which it is extracted. It is intended to provide typical values to allow comparison between metal alloy option rather than a definitive statement of mechanical performance or suitability for a particular application as these will vary with temperature, product type and product application. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of business.

ONE STOP SOLUTION FOR METAL PARTS