



Material - DIN EN 12164 CuZn40Mn1Pb1AlFeSn (CW721R)

Standard Specification for Copper and Copper Alloy Rod for Free Machining Purpose

Group - Non Ferrous Copper Alloys

Sub Group - DIN EN 12164 CuZn40Mn1Pb1AlFeSn Copper and Copper Alloy Rod for Free Machining Purpose Application - Intended for Valve, Pump, General Engineering, Automotive and Other Industries Grade Belongs to the Industry - Rod

Chemical Composition			Heat Treatment	
Aluminium	Al %	0.300 - 1.300		
Iron	Fe %	0.200 - 1.200		
Manganese	Mn %	0.800 - 1.800	As Raw or Solution Heat Treated	
Nickel	Ni %	0.300 max.		
Lead	Pb %	0.800 - 1.600		
Tin	Sn %	0.200 - 1.000		
Other	Ot %	0.300 max.		
Copper	Cu %	57.000 - 59.000		
Zinc	Zn %	Balance	Mechanical Properties	
-	-		Tensile Strength in Mpa	440 min.
-	-	-	Yield Strength in Mpa	200 min.
-	-	-	Elongation in %	10 min.
-	-	-	Reduction of Area in %	-
-	-	-	Hardness in HV	120 min.
-	-		Impac <mark>t in Joule</mark>	-

Cross Reference Table				
Material	Standard	Country	Grade Belong to the Industry	
CuZn40Mn1Pb1AlFeSn	BS	British	Rod	
CW721R	BS	British	Rod	
CuZn40Mn1Pb1AlFeSn	PN	Poland	Rod	
CW721R	PN	Poland	Rod	
CuZn40Mn1Pb1AlFeSn	SS	Sweden	Rod	
CW721R	SS	Sweden	Rod	
CW721R	DIN	Germany	Rod	

Further any inquiry to discuss with Gravity Cast Pvt. Ltd. – Gravity Group of Companies team member Call on +918469160029, or email marketing@gravitycastindia.com

All information in our data sheets and website is indicative only and is not intended to be a substitute for the full specification from which it is extracted. It is intended to provide typical values to allow comparison between metal alloy option rather than a definitive statement of mechanical performance or suitability for a particular application as these will vary with temperature, product type and product application. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of business.