

Material - DIN EN 1982 CB484K

Standard Specification for Copper and Copper Alloys - Ingots and Castings

Group - Non-Ferrous Copper Alloy

Sub Group - DIN EN 1982 Copper and Copper Alloys - Ingots and Castings

Application - Intended for Valve, Pump, General Engineering, Automotive and Other Industries Grade Belongs to the Industry - Ingot and Casting

Chemical Composition			Heat Treatment	
Aluminium	Al %	0.010 max.		
Iron	Fe %	0.150 max.		
Manganese	Mn %	0.100 max.	As-Cast	
Nickel	Ni %	1.500 - 2.400		
Phosphorus	Р%	0.050 max.		
Lead	Pb %	0.200 max.		
Sulphur	S %	0.040 max.		
Antimony	Sb %	0.050 max.		
Silicon	Si %	0.010 max.	Mechanical Properties	
Tin	Sn %	11.300 - 13.000	Tensile Strength in Mpa	280 - 300
Zinc	Zn %	0.300 max.	Yield Strength in Mpa	160 - 180
Cu + Ni	Cu%+Ni%	84.000 - 87.000	Elongation in %	8 - 12
-	-	-	Reduction of Area in %	-
-	-	-	Hardness in HB	85 - 95
-	-	-	Impac <mark>t in Joule</mark>	-

Cross Reference Table				
Material	Standard	Country	Grade Belong to the Industry	
CC484K	BS	British	Ingot and Casting	
СВ484К	ONORM	Australia	Ingot and Casting	
CuSn12Ni2-B	ONORM	Australia	Ingot and Casting	
СВ484К	UNI	Italy	Ingot and Casting	
CuSn12Ni2-B	UNI	Italy	Ingot and Casting	
CuSn12Ni2-B	DIN	Germany	Ingot and Casting	
CuSn12Ni2-B	UNE	Spain	Ingot and Casting	

Further any inquiry to discuss with Gravity Cast Pvt. Ltd. – Gravity Group of Companies team member Call on +918469160029, or email marketing@gravitycastindia.com

All information in our data sheets and website is indicative only and is not intended to be a substitute for the full specification from which it is extracted. It is intended to provide typical values to allow comparison between metal alloy option rather than a definitive statement of mechanical performance or suitability for a particular application as these will vary with temperature, product type and product application. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of business.

ONE STOP SOLUTION FOR METAL PARTS