

Material - DIN EN 1982 CuSn12-C

Standard Specification for Copper and Copper Alloys - Ingots and Castings

Group - Non-Ferrous Copper Alloy

Sub Group - DIN EN 1982 Copper and Copper Alloys - Ingots and Castings

Application - Intended for Valve, Pump, General Engineering, Automotive and Other Industries Grade Belongs to the Industry - Ingot and Casting

Chemical Composition			Heat Treatment	
Aluminium	Al %	0.010 max.	As-Cast	
Iron	Fe %	0.200 max.		
Manganese	Mn %	0.200 max.		
Nickel	Ni %	2.000 max.		
Phosphorus	P %	0.600 max.		
Lead	Pb %	0.700 max.		
Sulphur	S %	0.050 max.		
Antimony	Sb %	0.150 max.		
Silicon	Si %	0.010 max.	Mechanical Properties	
Tin	Sn %	11.000 - 13.000	Tensile Strength in Mpa	260 - 300
Zinc	Zn %	0.500 max.	Yield Strength in Mpa	140 - 150
Cu + Ni	Cu%+Ni%	85.000 - 88.500	Elongation in %	5 - 7
	-	-	Reduction of Area in %	-
-	-	-	Hardn <mark>ess in H</mark> B	80 - 90
-	-	-	Impac <mark>t in Joule</mark>	-

Cross Reference Table				
Material	Standard	Country	Grade Belong to the Industry	
CB483K	BS	British	Ingot and Casting	
CC483K	AFNOR NF	France	Ingot and Casting	
CC483K	ONORM	Australia	Ingot and Casting	
CC483K	BDS	Bulgaria	Ingot and Casting	
CC483K	UNI	Italy	Ingot and Casting	
CuSn12-C	UNE	Spain	Ingot and Casting	
CuSn12-C	MSZ	Hungary	Ingot and Casting	

Further any inquiry to discuss with Gravity Cast Pvt. Ltd. – Gravity Group of Companies team member Call on +918469160029, or email marketing@gravitycastindia.com

All information in our data sheets and website is indicative only and is not intended to be a substitute for the full specification from which it is extracted. It is intended to provide typical values to allow comparison between metal alloy option rather than a definitive statement of mechanical performance or suitability for a particular application as these will vary with temperature, product type and product application. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of business.

ONE STOP SOLUTION FOR METAL PARTS